

# ALUTECH

Technical catalogue

## PATIO SYSTEMS

| ALT SL130

**ALUTECH**  
GROUP OF COMPANIES







**ALUTECH SL130**  
Patio systems

# CONTENTS

Information pictograms and symbols . . . . .	.01.01
Materials. . . . .	.01.02

<b>System description</b> . . . . .	.02.01
-------------------------------------	--------

## **Order information**

Aluminium profiles . . . . .	.03.01
Accessories in lengths . . . . .	.03.06
Gaskets . . . . .	.03.07
Aluminium items. . . . .	.03.09
Non-aluminium items . . . . .	.03.12
Non-aluminium items (sets) . . . . .	.03.19
Accessories . . . . .	.03.24
Hardware . . . . .	.03.25
Equipment . . . . .	.03.35
Chemical products . . . . .	.03.41

<b>Main profile characteristics</b> . . . . .	.04.01
---	--------

<b>Table of glazing</b> . . . . .	.05.01
-----------------------------------	--------

<b>Sections and junctions</b> . . . . .	.06.01
---	--------







<b>Calculation examples</b> . . . . .	.07.01
---------------------------------------	--------

<b>Profile machining and assembly</b> . . . . .	.08.01
---	--------

<b>Hardware installation</b> . . . . .	.09.01
--	--------




Pictograms



### How to use the catalogue

Joint type	External section	Article	Package quantity – 140 pcs
Internal section		AYPC.SL130.0952	14
		AYPC.W50.0929-01	80
90° angle joint		5x10 DIN6325D	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0945	4 4 4
90° transom bar joint			
90° angle joint			
Horizontal extension		AYPC.SL130.0953, AYPC.SL130.0954	2 2
Joint			





## Aluminium profiles

Aluminium profiles are made in compliance with EN 1202-2, EN 755-1, EN 755-2, EN 573:3, EN 486:2009 using 6060 and 6063 alloys of T6 or T66 temper. The alloys are corrosion resistant and are suitable for manufacture of profiles with high accuracy.

## Polyamide thermal breaks

The combined profiles have thermal bridges made of glass-filled polyamide produced by the leading manufacturers. Excellent strength characteristics are provided by modern technology of joining the dissimilar materials.

## Gaskets

EPDM gaskets are used to seal the infill area and central area to provide condensed water removal and sealing of leaf-to-leaf and leaf-to-frame joints.

## Fixing elements

Fasteners used to connect profiles, components and accessories must be made of stainless steel.

## Steel rods

The bearing rods take up the load from the weight of the door leaves and are also exposed to weather conditions. Therefore, they are made of stainless steel according to DIN EN 10305 part 3/5, DIN EN 10162 and EN 10021 for cold-rolled profiles made of steel.

## Powder coating

Various types of coatings protect profiles from corrosion:

- protective and decorative powder coating of minimum 60 µm in thickness, Qualicoat/Seaside certified, available in any RAL colour;
- wood grain effect coating – decorative powder coating of the aluminium profile using special equipment. Qualicoat/Seaside certified. 5 wood grain effect colours are available.

## Anodizing

Anodizing is available in 9 standard colours. Several surface treatment options are available: chemical etching, shot blasting and brushing. Anodizing is certified by Qualanod quality standard.





**ALUTECH SL130**  
Patio systems

# SYSTEM DESCRIPTION







ALT SL130 system is an exclusive solution for both private houses and public facilities designed to arrange cafe or restaurant terraces or hotel balconies. In the opened position the door leaves provide an easy access to the premises as well as help to save the usable room space.




The variety of opening options is provided by the assortment of frame profiles and required kits of ledge components.

Depending on the region and operational requirements as well as client's preferences, SL130 system has two opening options: lift & slide and sliding. Lift & slide option is suitable for houses and premises that are used all year round where absence of draughts and high structural tightness are essential. The sliding option is more simple solution for the premises with no strict requirements. Both of the two available hardware options are supplied by the leading European manufacturers and ensure smooth operation of the door leaves as well as their reliability and long service life.

Taking into account the variety of projects' design and preferences of customers from different regions, we have implemented several SL130 assembly options: frame profiles may be cut at 90° or 45°. The first option ensures easy assembly and installation of large patio doors in multi-storey buildings. The option of 45° has its advantages for the in-house assembly.



SL130 system is available in classic design with standard leaves as well as in Slim Line design – slim interlock option. Modern patio system solution with available profile options allows to enlarge the transparent area of the door preserving its high inertia characteristics.



Adjustable coupling profile connection along the door length is a unique feature of SL130. Due to this, the final adjustment of the door leaves while installation may be performed on site. This solution is essential for wide door leaves or patios with many leaves.



Polyamide 32 mm wide thermal breaks are used in main system profiles and provide high energy efficiency of the door.

ALT SL130 system is designed for installation of energy efficient double- and triple-glazed units. Maximum thickness of the infill unit is up to 42 mm. Glass beads are always installed from the inside of the premises.

Excellent resistance of SL130 lift & slide doors to weather conditions is ensured by combination of the ledge gaskets and connecting corners that together form two closed sealing contours along the leaf as well as by a full kit of coupling details provided in ledge kits.

EPDM gaskets resistant to weather impact are used to provide maximum insulation for the infill unit installation area.

ALT SL130 system is designed in three opening types: single, double and triple track. Depending on the opening type chosen, the patio can consist of up to four door leaves.

Maximum door leaf height and width depend on the applied loads, number of storeys in a building and its function. But the system is limited by 3.3 metres in height and 3.2 metres in width for lift and slide type and 2.7 metres in height and 2.3 metres in width for sliding type.

Due to system characteristics, minimum door leaf width is 650 mm.

Maximum leaf weight depends on the opening type: 420 kg for lift and slide doors and 270 kg for sliding doors.

Special hardware with auxiliary locking points is used in ALT SL130 patio system to enhance its burglar resistance.

There are three types of handle design available for order.

HS-series handles are available in three options:

- single-sided without cylinder;
- single-sided with cylinder;
- double-sided with cylinder.

PASK handles are available for order in four design options:

- single-sided without cylinder cover;
- single-sided with key;
- single-sided with cylinder cover;
- double-sided with cylinder cover.

To match the colour of the patio door, the hardware handles are available in three colours.











**ALUTECH SL130**  
Patio systems










## ORDER INFORMATION










Aluminium profiles . . . . .	.03.01
Accessories in lengths. . . . .	.03.06
Gaskets . . . . .	.03.07
Aluminium items. . . . .	.03.09
Non-aluminium items . . . . .	.03.12
Non-aluminium items (sets) . . . . .	.03.19
Accessories. . . . .	.03.24
Hardware . . . . .	.03.25
Equipment . . . . .	.03.35
Chemical products . . . . .	.03.41
















Name, article, drawing	Profile colour	Code	Wight, kg/m	Bar length, m	Exterior perimeter, mm	Moment of inertia, cm <sup>4</sup>		Moment of resistance, cm <sup>3</sup>		Quantity in pack		Gross pack weight, kg
						Jx	Jy	Wx	Wy	pcs	m	
Frame profile AYPC.SL130.0101 	00 RAL 9016 RAL 9006 A00-D6	13601800 13601821 13601831 136018808	2.742	6.5	560.0	20.2	116.9	8.90	17.99	1	6.5	17.82 18.35 18.35 17.82
Frame profile AYPC.SL130.0102 	00 RAL 9016 RAL 9006 A00-D6	13601900 13601921 13601931 136019808	2.637	6.5	559.0	20.0	108.7	8.85	16.73	1	6.5	16.96 17.47 17.47 16.96
Frame profile AYPC.SL130.0103 	00 RAL 9016 RAL 9006 A00-D6	13600100 13600121 13600131 136001808	2.684	6.5	628.9	14.7	107.2	5.39	15.54	2	13	17.44 17.96 17.96 17.44
Frame profile AYPC.SL130.0104 	00 RAL 9016 RAL 9006 A00-D6	13602200 13602221 13602231 136022808	2.563	6.5	620.9	14.5	100.2	5.31	14.57	2	13	33.32 34.32 34.32 33.32
Frame profile AYPC.SL130.0105 	00 RAL 9016 RAL 9006 A00-D6	13600200 13600221 13600231 136002808	2.495	6.5	649.4	11.8	100.4	4.51	14.66	2	13	32.44 33.41 33.41 32.44
Frame profile AYPC.SL130.0106 	00 RAL 9016 RAL 9006 A00-D6	13602000 13602021 13602031 136020808	2.479	6.5	703.0	16.1	109.5	7.04	16.85	1	6.5	16.11 16.59 16.59 16.11
Frame profile AYPC.SL130.0107 	00 RAL 9016 RAL 9006 A00-D6	13602300 13602321 13602331 136023808	4.037	6.5	855.0	24.6	369.8	9.72	35.14	1	6.5	26.24 27.03 27.03 26.24
Frame profile AYPC.SL130.0108 	00 RAL 9016 RAL 9006 A00-D6	136024.00 136024.21 136024.31 136024.808	3.852	6.5	855.6	24.3	346.6	9.61	32.86	1	6.5	24.98 25.72 25.72 24.98












Name, article, drawing	Profile colour	Code	Wight, kg/m	Bar length, m	Exterior perimeter, mm	Moment of inertia, cm <sup>4</sup>		Moment of resistance, cm <sup>3</sup>		Quantity in pack		Gross pack weight, kg
						Jx	Jy	Wx	Wy	pcs	m	
Adapter AYPC.SL130.0503 	00 RAL 9016 RAL 9006 A00-D6	13602900 13602921 13602931 136029808	1885	6.5	527.0	7.6	89.0	3.25	11.97	2	13	24.51 25.24 25.24 24.51
Glass bead profile AYPC.SL130.0601 	00 RAL 9016 RAL 9006 A00-D6	13603000 13603021 13603031 136030808	0.204	6.5	86.5	-	-	-	-	18	117	3.67 3.78 3.78 3.67
Glass bead profile AYPC.SL130.0602 	00 RAL 9016 RAL 9006 A00-D6	13600600 13600621 13600631 136006808	0.212	6.5	108.2	-	-	-	-	18	117	3.82 3.93 3.93 3.82
Glass bead profile AYPC.SL130.0603 	00 RAL 9016 RAL 9006 A00-D6	13602100 13602121 13602131 136021808	0.251	6.5	136.7	-	-	-	-	18	117	4.52 4.65 4.65 4.52
Glass bead profile AYPC.SL130.0604 	00 RAL 9016 RAL 9006 A00-D6	13603100 13603121 13603131 136031808	0.28	6.5	142.2	-	-	-	-	18	117	5.04 5.19 5.19 5.04
Glass bead profile AYPC.SL130.0605 	00 RAL 9016 RAL 9006 A00-D6	13603200 13603221 13603231 136032808	0.294	6.5	163.7	-	-	-	-	18	117	5.29 5.44 5.44 5.29
Ledge profile AYPC.SL130.0611 	00 RAL 9016 RAL 9006 A00-D6	13600700 13600721 13600731 136007808	0.206	6.5	98.8	-	-	-	-	18	117	23.86 24.57 24.57 23.86
Extruded aluminium profile AYPC.SL130.0701 	00	13601500	0.730	6.5	160.3	-	-	-	-	4	26	18.99
Reinforcing profile AYPC.SL130.0702 	00	13603400	1.177	6.5	243.4	1.9	8.7	1.38	3.63	4	26	30.60











Name, article, drawing	Profile colour	Code	Wight, kg/m	Bar length, m	Exterior perimeter, mm	Moment of inertia, cm <sup>4</sup>		Moment of resistance, cm <sup>3</sup>		Quantity in pack		Gross pack weight, kg
						Jx	Jy	Wx	Wy	pcs	m	
End profile AYPC.SL130.0801 	00 RAL 9016 RAL 9006 A00-D6	13603300 13603321 13603331 136033808	0.363	6.5	182.9	-	-	-	-	4	26	9.43 9.71 9.71 9.43
End profile AYPC.SL130.0802 	00 RAL 9016 RAL 9006 A00-D6	13600800 13600821 13600831 136008808	0.323	6.5	126.2	-	-	-	-	8	52	16.80 17.30 17.30 16.80
Slope profile AYPC.SL130.0803 	00 RAL 9016 RAL 9006 A00-D6	13600900 13600921 13600931 136009808	0.653	6.5	245.9	-	-	-	-	8	52	34.53 35.56 35.56 34.53
Slope profile AYPC.SL130.0804 	00 RAL 9016 RAL 9006 A00-D6	13601000 13601021 13601031 136010808	0.420	6.5	207.0	-	-	-	-	8	52	21.86 22.51 22.51 21.86
Threshold profile AYPC.SL130.0805 	00 RAL 9016 RAL 9006 A00-D6	13601100 13601121 13601131 136011808	0.502	6.5	261.8	-	-	-	-	6	39	19.59 20.17 20.17 19.59
Slope profile AYPC.SL130.0805-01 	00 RAL 9016 RAL 9006 A00-D6	13601200 13601221 13601231 136012808	0.459	6.5	258.0	-	-	-	-	8	52	23.87 24.58 24.58 23.87
Cover cap profile AYPC.SL130.0806 	00 RAL 9016 RAL 9006 A00-D6	13601300 13601321 13601331 136013808	0.093	6.5	69.9	-	-	-	-	20	130	12.05 12.41 12.41 12.05
Drain profile AYPC.SL130.0807 	00 RAL 9016 RAL 9006 A00-D6	13603500 13603521 13603531 136035808	0.252	6.5	93.7	-	-	-	-	4	26	6.54 6.73 6.73 6.54
Reinforcing profile AYPC.SL160.0702 	00 RAL 9016 RAL 9006 A00-D6	12602000 12602021 12602031 126020808	1574	6.5	285.8	49.4	11.2	113.4	5.6	2	13	3.15 3.24 3.24 3.15











Name, article, drawing	Profile colour	Code	Wight, kg/m	Bar length, m	Exterior perimeter, mm	Moment of inertia, cm <sup>4</sup>		Moment of resistance, cm <sup>3</sup>		Quantity in pack		Gross pack weight, kg
						Jx	Jy	Wx	Wy	pcs	m	
Reinforcing profile AYPC.SL160.0705 	00 RAL 9016 RAL 9006 A00-D6	12605400 12605421 12605431 126054808	0.995	6.5	188.8	14	3.4	4.91	2.43	4	26	3.98 4.09 4.09 3.98
Corner crimping profile AYPC.EF65.0802 	00	11709600	3.048	3.25	358.9	-	-	-	-	2	6.5	19.81
Corner crimping profile AYPC.W50.0703 	00	12402300	2.982	3.25	380.0	-	-	-	-	2	6.5	19.38
Extruded aluminium profile AYPC.W72.0701 	00	10904100	3.753	3.25	3911	-	-	-	-	2	6.5	24.4
Cover profile AYPC.111.0605 	00 RAL 9016 RAL 9006 A00-D6	10503000 10503021 10503069 105030808	0.09	6.2	79.3	-	-	-	-	4	24.8	2.19 2.26 2.26 2.19



Name, article, drawing	Colour	Code	Weight, kg/m	Bar length, m	Pack quantity		Gross pack weight, kg
					pcs	m	
Fixing profile AYPCL130.1901 	-	13651100	0.161	3.25	1	3.25	0.55
Frame ledge profile AYPCL130.1902 	-	13651200	0.283	5.50	1	5.50	1.60
Frame ledge profile AYPCL130.1903 	-	13651300	0.151	5.50	1	5.50	1.0
Cover profile AYPCL130.1904 	-	13651400	0.091	5.80	1	5.80	0.55
Cover profile AYPCL130.1905 	-	13651500	0.127	5.80	1	5.80	0.75
Spacer profile AYPCL130.1906 	-	13651600	0.101	3.25	1	3.25	0.35
Decorative profile AYPCL130.1907 	-	13657700	0.250	2.50	1	2.50	0.625
Guide rail AYPCL160.1950 	-	12652800	0.197	6.50	1	6.5	1.30











Name, article, drawing	Colour	Code	Weight, kg/m	Quantity in pack, m	Gross pack weight, kg
EPDM gasket FRK29-01 	-	10415900	0.043	400	17.80
EPDM wedge gasket FRK38 	-	10415500	0.046	400	18.70
EPDM rebate gasket FRK175 	-	12620100	0.044	300	13.50
EPDM gasket FRK176 	-	12620200	0.035	150	6.00
EPDM gasket FRK188 	-	12620300	0.037	350	13.25
EPDM wedge gasket FRK191 	-	10830300	0.067	125	8.62
EPDM wedge gasket FRK192 	-	10830500	0.097	100	9.98
EPDM wedge gasket FRK193 	-	10830700	0.105	100	11.14













Name, article, drawing	Colour	Code	Weight, kg/m	Quantity in pack, m	Gross pack weight, kg
<p>EPDM wedge gasket FRK194</p> 	-	10831200	0.135	75	9.80
<p>EPDM gasket FRK230</p> 	-	13620100	0.040	150	7.20
<p>Felt sealing IS10</p> 	-	1112505	0.006	325	2.11
<p>Felt sealing ISE 01</p> 	-	1112511	0.007	225	2.25
<p>Felt sealing AYPC.SL130.0912</p> 	-	13620200	-	-	-








Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Original profile	Delivery set contents	
								Article	Quantity, pcs
Transom fixing element AYPC.SL130.0950	00	13650400	0.010	pcs	130	130	AYPC.SL130.0701	Corner cleat AYPC.SL130.1701 Self-tapping screw 3.5x19-A2IS014586 Pin 5x8DIN6325D	1 1 2
								For profiles	
								AYPC.SL130.0202, AYPC.SL130.0203, AYPC.SL130.0204	
Transom fixing element AYPC.SL130.0950-01	00	13650500	0.013	pcs	130	169	AYPC.SL130.0701	Corner cleat AYPC.SL130.1701-01 Self-tapping screw 3.5x19-A2IS014586 Pin 5x8DIN6325D	1 1 2
								For profiles	
								AYPC.SL130.0301	
Transom fixing element AYPC.SL130.0950-02	00	13650600	0.027	pcs	65	176	AYPC.SL130.0701	Corner cleat AYPC.SL130.1701-02 Self-tapping screw 3.5x19-A2IS014586 Pin 5x10DIN6325D	1 2 2
								For profiles	
								AYPC.SL130.0201	
Corner cleat AYPC.W50.0929-01	00	12430900	0.078	pcs	80	6.24	AYPC.W50.0703	-	-
								For profiles	
								AYPC.SL130.0102, AYPC.SL130.0104, AYPC.SL130.0108	
Corner cleat AYPC.SL130.0951	00	13650700	0.041	pcs	96	3.96	AYPC.W72.0701	-	-
								For profiles	
								AYPC.SL130.0201	










Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Original profile	Delivery set contents	
								Article	Quantity, pcs
Corner cleat AYPC.SL130.0952	00	13650800	0.043	pcs	14	6.02	AYPC.EF65.0802	-	-
								For profiles	
								AYPC.SL130.0104, AYPC.SL130.0108	
Corner cleat AYPC.SL130.0952-01	00	13650900	0.079	pcs	51	4	AYPC.EF65.0802	-	-
								For profiles	
								AYPC.SL130.0108	
Corner cleat AYPC.SL130.0952-02	00	13651000	0.235	pcs	17	3.99	AYPC.EF65.0802	-	-
								For profiles	
								AYPC.SL130.0108	
Frame connector set AYPC.SL130.0953	00	13657100	0.39	pcs	1	0.78	AYPC.SL130.1703	Frame connector AYPC.SL130.1703 Screw M5x8-A2DIN7991 Encapsulating insert AYPC.SL130.0943	2 8 4
								For profiles	
								AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108	
Frame connector set AYPC.SL130.0954	00	13657200	0.1	pcs	1	0.2	AYPC.SL130.1704	Frame connector AYPC.SL130.1704 Screw M5x8-A2DIN7991 Encapsulating insert AYPC.SL130.0945	2 4 4
								For profiles	
								AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108,	













Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Original profile	Delivery set contents	
								Article	Quantity, pcs
Frame connector set AYPC.SL130.0955	00	13657300	0.59	pcs	1	1.18	AYPC.SL130.1705	Frame connector AYPC.SL130.1705 Screw M5x8-A2DIN7991 Encapsulating insert AYPC.SL130.0943 Encapsulating insert AYPC.SL130.0946	2 8 4 6
								For profiles	
								AYPC.SL130.0107, AYPC.SL130.0108	
Chevron AYPC.W62.0957	00	10813600	0.003	pcs	200	0.68	-	-	-
								For profiles	
								AYPC.SL130.0503	












Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
<p>Fixator AYPC.SL130.0905</p> 	-	13651700	0.053	pcs	30	1.65	<p>The set does not include self-tapping screws 4.8x45-A2ISO14585 3.9x25-A2ISO14585</p> 
<p>Bearing support AYPC.SL130.0906</p> 	-	13651800	0.006	pcs	60	0.40	
<p>Drain plug AYPC.SL130.0907</p> 	-	13653900	0.003	pcs	10	0.07	
<p>Drain cap set AYPC.SL130.0908</p> 	10 (black)	13657800	0.004	pcs	20	0.09	
	01 (white)	13657801					
<p>Support set AYPC.SL130.0910K</p> 	-	13657600	0.086	pcs	1	0.09	



Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
Corner AYPCL130.0918 	-	13651900	0.006	pcs	120	0.8	
Cover AYPCL130.0925 	-	13652000	0.008	pcs	20	0.17	
Interlock plug set AYPCL130.0933K 	-	13657500	0.010	pcs	2	0.02	
Face seal AYPCL130.0981 	-	13652600	0.001	pcs	100	0.11	
Face seal set AYPCL130.0982 	-	13657900	0.018	pcs	3	0.06	
Face seal set AYPCL130.0983 	-	13658000	0.028	pcs	3	0.09	
Decorative plug $\varnothing 10$ AYPCL160.0928 	10 (black)	12655100	0.002	pcs	100	0.3	
	01 (white)	12655101					










Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
Bearing support AYPC.W62.0901M 	-	10815800	0.015	pcs	100	15	
Leveling support 100x22x2 100x22x5 	-	10461000 10461300	0.02 0.02	pcs	100	2.0 2.0	
Leveling support 100x32x1 100x32x2 100x32x3 100x32x5 	-	11213400 11213500 11213600 10840300	0.003 0.004 0.005 0.007	pcs	1000	3.0 4.0 5.0 7.0	
Leveling support 100x38x1 100x38x2 100x38x3 	-	11213700 11213800 11213900	0.006 0.006 0.007	pcs	1000	6.0 6.0 7.0	
Leveling support 100x44x1 100x44x2 100x44x3 100x44x5 	-	11218100 11218200 11218300 11219800	0.005 0.005 0.006 0.008	pcs	1000	5.0 5.0 6.0 8.0	
Leveling support 100x50x1 100x50x2 100x50x3 100x50x4 100x50x5 	-	11218400 11218500 11218600 10840500 10840600	0.006 0.006 0.007 0.008 0.009	pcs	1000	6.0 6.0 7.0 8.0 9.0	









Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
Cover AYPC.SL160.0925 	-	12654700	0.011	pcs	30	0.33	
Water drain plug AYPC.100P.1850 	-	10183500	0.001	pcs	50	0.04	
Corner AYPC.W62.0912 	-	10816900	0.005	pcs	120	0.54	
Corner AYPC.W62.0913 	-	10817000	0.006	pcs	120	0.75	
End cap set AYPC.W62.0914 	-	10819000	0.002	pcs	120	0.75	







Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
<p>Fixing lug AYPC.W62.0940</p> 	-	10828400	0.042	pcs	100	4.20	
<p>Fixing lug AYPC.W62.0940-01</p> 	-	10828500	0.051	pcs	100	5.10	
<p>Water drain plug AYPC.W62.0945</p> 	-	10831500	0.007	pcs	50	0.37	
<p>Water drain plug AYPC.W62.0946</p> 	-	10831700	0.003	pcs	40	0.10	
<p>EPDM corner FRK170</p> 	-	10915200	0.003	pcs	100	0.30	
<p>EPDM corner FRK177</p> 	-	12654100	0.002	pcs	24	0.05	





Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
EPDM corner FRK178 	-	12654200	0.002	pcs	24	0.05	
EPDM corner FRK178-01 	-	12654300	0.002	pcs	24	0.05	
Encapsulating insert AYPC.SL130.0943 	-	13652100	0.024	pcs	20	0.50	 For profiles AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108,
Encapsulating insert AYPC.SL130.0944 	-	13652200	0.052	pcs	20	1.06	 For profiles AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108
Encapsulating insert AYPC.SL130.0945 	-	13652300	0.011	pcs	20	0.26	 For profiles AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108
Encapsulating insert AYPC.SL130.0946 	-	13652400	0.054	pcs	20	1.10	 For profiles AYPC.SL130.0107, AYPC.SL130.0108, AYPC.SL130.0109





Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Notes
<p>Encapsulating insert AYPC.SL130.0947</p> 	-	13652500	0.096	pcs	20	195	 <p>For profiles AYPC.SL130.0109</p>




Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Delivery set contents
Frame ledge set AYPC.SL130.0940HS	-	13655600	0.23	pcs	1	0.23	AYPC.SL130.0901 – 2 pcs 3.9x9.5-A2ISO14586 – 4 pcs AYPC.F50.0932 – 1 pc 
							AYPC.SL130.0916 
							AYPC.SL130.0914 
							AYPC.SL160.0904 – 6 pcs M4x10-A2ISO4027 – 6 pcs 
							AYPC.SL130.0904 – 1 pc AYPC.SL130.0904-01 – 1 pc 3.5x13-A2ISO14586 – 4 pcs 
Frame ledge set AYPC.SL130.0940HS-01	-	13655700	0.12	pcs	1	0.12	AYPC.SL130.0901 – 2 pcs 3.9x9.5-A2ISO14586 – 4 pcs AYPC.F50.0932 – 1 pc 
							AYPC.SL130.0916 
							AYPC.SL130.0914 
							AYPC.SL160.0904 – 6 pcs M4x10-A2ISO4027 – 6 pcs 
							AYPC.SL130.0902 AYPC.SL130.0902-01 3.9x9.5-A2ISO14586 – 2 pcs 
AYPC.SL130.0903 AYPC.SL130.0903-01 3.5x13-A2ISO14586 – 2 pcs 3.9x9.5-A2ISO14586 – 2 pcs 							





Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Delivery set contents
<p>Frame ledge set AYPC.SL130.0940S</p> 	-	13655800	0.098	pcs	1	0.1	<p>AYPC.SL130.0901 - 2 pcs 3.9×9.5-A2 ISO14586 - 4 pcs AYPC.F50.0932 - 1 pc</p> 
							<p>AYPC.SL130.0984 - 2 pcs</p> 
							<p>AYPC.SL130.0909 - 6 pcs M4×10-A2ISO4027 - 6 pcs</p> 
							<p>AYPC.SL130.0904 AYPC.SL130.0904-01 3.5×13-A2 ISO14586 - 4 pcs</p> 
<p>Frame ledge set AYPC.SL130.0940S-01</p> 	-	13655900	0.124	pcs	1	0.124	<p>AYPC.SL130.0901 - 2 pcs 3.9×9.5-A2ISO14586 - 4 pcs AYPC.F50.0932 - 1 pc</p> 
							<p>AYPC.SL130.0984 - 2 pcs</p> 
							<p>AYPC.SL130.0909 - 6 pcs M4×10-A2ISO4027 - 6 pcs</p> 
							<p>AYPC.SL130.0902 AYPC.SL130.0902-01 3.9×9.5-A2ISO14586 - 2 pcs</p> 
							<p>AYPC.SL130.0903 AYPC.SL130.0903-01 3.5×13-A2ISO14586 - 2 pcs 3.9×9.5-A2ISO14586 - 2 pcs</p> 

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Delivery set contents
Sealing block AYPC.SL130.0941HS	-	13656000	0.34	pcs	1	0.34	AYPC.SL130.0913 - 1 pc 3.9x9.5-A2ISO14585 - 2 pcs 
							AYPC.SL130.0915-01 
							For profiles
							AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0107, AYPC.SL130.0108
Sealing block AYPC.SL130.0941HS-01	-	13656100	0.3	pcs	1	0.3	AYPC.SL130.0913 - 1 pc 3.9x9.5-A2ISO14585 - 2 pcs 
							AYPC.SL130.0915 
							For profiles:
							AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0107, AYPC.SL130.0108





Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Delivery set contents
Sealing block AYPC.SL130.094.2HS	-	13656400	0.23	pcs	1	0.23	<p>AYPC.SL130.0913-01 - 1 pc 3.9x9.5-A2ISO14585 - 2 pcs</p> 
							AYPC.SL130.0932-01
For profiles:							
AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108							
Sealing block AYPC.SL130.094.2HS-01	-	13656500	0.2	pcs	1	0.2	<p>AYPC.SL130.0913-01 - 1 pc 3.9x9.5-A2ISO14585 - 2 pcs</p> 
							AYPC.SL130.0932
For profiles:							
AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108							




Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg	Delivery set contents
Sealing block gasket AYPC.SL130.0985  	-	13655200	0.009	pcs	2	0.05	-
							For profiles:  AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0107, AYPC.SL130.0108
Sealing block gasket AYPC.SL130.0985-01  	-	13655300	0.011	pcs	2	0.06	-
							For profiles:  AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108
Sealing block gasket AYPC.SL130.0986  	-	13655400	0.017	pcs	2	0.0800	-
							For profiles:  AYPC.SL130.0101, AYPC.SL130.0102, AYPC.SL130.0107, AYPC.SL130.0108
Sealing block gasket AYPC.SL130.0986-01  	-	13655500	0.014	pcs	2	0.07	-
							For profiles:  AYPC.SL130.0103, AYPC.SL130.0104, AYPC.SL130.0107, AYPC.SL130.0108




Name, drawing	Article	Colour	Code	Weight, kg/100 pcs	Measure unit	Quantity in pack	Gross pack weight, kg	
Self-tapping screw 	3.9x9.5-A2IS014585	-	18101000	0.105	100 pcs	1	0.135	
	3.9x13-A2IS014585		18100600	0.140			0.170	
	3.9x25-A2IS014585		18102300	0.205			0.235	
	4.8x16-A2IS014585		18101200	0.244			0.253	
	4.8x45-A2IS014585		18105000	0.530			0.56	
Self-tapping screw with hidden head 	2.9x9.5-A2IS014586	-	18105300	0.038	100 pcs	1	0.068	
	3.5x19-A2IS014586							
	3.9x13-A2IS014586		18100700	0.088			0.118	
	3.9x19-A2IS014586		18102100	0.165			0.205	
	3.9x25-A2IS014586		18105200	0.164			0.194	
	3.9x38-A2IS014586		18102900	0.202			0.232	
	4.8X32-A2IS014586		18140500	0.335			0.365	
	4.8X60-A2IS014586		18119400	0.575			0.605	
	4.8X70-A2IS014586		18119500	0.675			0.705	
Screw 	M5x8-A2DIN7991	-	18140800	0.210	100 pcs	1	0.240	
Pin 	5x8DIN6325D	-	18101700	0.264	100 pcs *Supplied exclusively by Alutech Group. Can be replaced with DIN6325	1	0.294	
	5x10DIN6325D	-	18112400	0.135		1	0.137	
	5x14DIN6325D	-	18140600	0.155		1	0.185	






Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Lift and slide roller set HS200 					-	193720	13279600	0.761	pcs	1	0.761
HS120	HS200	HS270	HS420	S270							
●	●										
Lift and slide roller set HS270 					-	485241	13279100	0.825	pcs	1	0.825
HS120	HS200	HS270	HS420	S270							
		●	●								
Additional roller set HS420 					-	485242	13279700	0.683	pcs	1	0.683
HS120	HS200	HS270	HS420	S270							
			●								
Slide roller set S270 					-	486356	13279800	0.516	pcs	1	0.516
HS120	HS200	HS270	HS420	S270							
				●							
Handle transmission HS120 Gr.180 					-	246866	13279900	1.011	pcs	1	1.011
HS120	HS200	HS270	HS420	S270							
●											
Handle transmission HS120 Gr.210 					-	246869	13370100	1.352	pcs	1	1.352
HS120	HS200	HS270	HS420	S270							
●											
Handle transmission HS120 Gr.240 					-	246872	13370200	1.588	pcs	1	1.588
HS120	HS200	HS270	HS420	S270							
●											






Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Handle transmission D25 HS120 INVISO Gr.180 					-	304758	13370300	1.167	pcs	1	1.167
HS120	HS200	HS270	HS420	S270							
●											
Handle transmission D25 HS120 INVISO Gr.210 					-	304759	13370400	1.431	pcs	1	1.431
HS120	HS200	HS270	HS420	S270							
●											
Handle transmission D25 HS120 INVISO Gr.240 					-	304760	13370500	1.581	pcs	1	1.581
HS120	HS200	HS270	HS420	S270							
●											
Handle transmission HS270 Gr.180 					-	195419	13370600	1.115	pcs	1	1.115
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission HS270 Gr.210 					-	195425	13370700	1.458	pcs	1	1.458
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission HS270 Gr.240 					-	195431	13370800	1.693	pcs	1	1.693
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission HS270 Gr.270 					-	195437	13370900	1.928	pcs	1	1.928
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission D27,5 HS270 INVISO Gr.180 					-	304092	13371000	1.281	pcs	1	1.281
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission D27,5 HS270 INVISO Gr.210 					-	304093	13371100	1.637	pcs	1	1.637
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission D27,5 HS270 INVISO Gr.240 					-	304094	13371200	1.753	pcs	1	1.753
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission D27,5 HS270 INVISO Gr.270 					-	304095	13277900	1.963	pcs	1	1.963
HS120	HS200	HS270	HS420	S270							
	●	●	●								






Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Handle transmission D25 S270 Gr.50 					-	215529	13371300	0.414	pcs	1	0.414
HS120	HS200	HS270	HS420	S270							
				●							
Handle transmission D25 S270 Gr.200 					-	215532	13371400	1.340	pcs	1	1.340
HS120	HS200	HS270	HS420	S270							
				●							
Handle transmission extension 					-	209738	13174200	0.575	pcs	1	0.575
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle transmission extension INVISIO 					-	302889	13373900	0.560	pcs	1	0.560
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Connecting rod 150S+ 					-	184578	13172700	0.327	pcs	1	0.327
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Connecting rod 200S+ 					-	184581	13172900	0.590	pcs	1	0.590
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Connecting rod 250S+ 					-	184584	13171900	0.810	pcs	1	0.810
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Connecting rod 323S+ 					-	184587	13173500	1.114	pcs	1	1.114
HS120	HS200	HS270	HS420	S270							
●	●	●	●								







Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Handle 161 EG 					RAL 9016 RAL 9005 A00-E6	206209	13371821 13371932 133717806	0.200	pcs	1	0.200
HS120	HS200	HS270	HS420	S270							
●				●							
Handle 161 EG-S 					RAL 9016 RAL 9005 A00-E6	206218	13372121 13372232 133720806	0.242	pcs	1	0.242
HS120	HS200	HS270	HS420	S270							
●				●							
Handle 161 EG-Pz/I 					RAL 9016 RAL 9005 A00-E6	206227	13372421 13372532 133723806	0.260	pcs	1	0.260
HS120	HS200	HS270	HS420	S270							
				●							
Handle 160 EG-Pz/A 					RAL 9016 RAL 9005 A00-E6	163275	13372721 13372832 133726806	0.225	pcs	1	0.225
HS120	HS200	HS270	HS420	S270							
				●							
External flush pull handle 					RAL 9016 RAL 9005 RAL 9006	223548	13373021 13373132 13372998	0.102	pcs	1	0.102
HS120	HS200	HS270	HS420	S270							
●				●							






Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Lock housing SF D25 					-	203130	13373200	0.123	pcs	1	0.123
HS120	HS200	HS270	HS420	S270							
				●							
Handle PSK Dublin 					RAL 9016 RAL 9005 A00-E2	128PSK	13100221 13100232 131002802	0.323	pcs	1	0.323
HS120	HS200	HS270	HS420	S270							
●				●							
Handle PSK Dublin with key 					RAL 9016 RAL 9005 A00-E2	129PSK	13100321 13100332 131003802	0.350	pcs	1	0.350
HS120	HS200	HS270	HS420	S270							
●				●							
External flush pull handle PSK 					RAL 9016 RAL 9005 A00-E2	128PSM	13100421 13100432 131004802	0.098	pcs	1	0.098
HS120	HS200	HS270	HS420	S270							
●				●							
Handle 					RAL 9016 RAL 9005 A00-E6	234410	13173721 13172632 13172690	0.772	pcs	1	0.772
HS120	HS200	HS270	HS420	S270							
	●	●	●								





Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Handle PZ/I 					RAL 9016 RAL 9005 A00-E6	234431	13173821 13173932 13173990	0.600	pcs	1	0.600
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Handle PZ/IE H 					RAL 9016 RAL 9005 A00-E6	185179	13172421 13175332 13172490	1.165	pcs	1	1.165
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Internal handle without cylinder hole 					RAL 9016 RAL 9005 A00-E2	128HS1	13108721 13108732 131092802	0.531 0.531 0.550	pcs	1	0.531 0.531 0.550
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Internal handle with cylinder hole 					RAL 9016 RAL 9005 A00-E2	128HS2	13108821 13108832 131093802	0.531 0.531 0.550	pcs	1	0.531 0.531 0.550
HS120	HS200	HS270	HS420	S270							
	●	●	●								
External handle with cylinder hole 					RAL 9016 RAL 9005 A00-E2	128HS3	13108921 13108932 131094802	0.697 0.697 0.714	pcs	1	0.697 0.697 0.714
HS120	HS200	HS270	HS420	S270							
	●	●	●								





Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
External flush pull handle 					RAL 9016 RAL 9005 A00-E2	129HS	13109021 13109032 131095802	0.259 0.259 0.202	pcs	1	0.259 0.259 0.202
HS120	HS200	HS270	HS420	S270							
	●	●	●								
INVISO hook with strike plate 					-	305427 305428	13373300 13373400	0.184 0.294	pcs	1 2	0.184 0.294
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Locking bolt with positioning 103 S+ 					-	214401	13373500	0.025	pcs	1	0.025
HS120	HS200	HS270	HS420	S270							
●	●	●	●	●							
Locking bolt with positioning and microventilation 103 S+ 					-	214404	13373600	0.028	pcs	1	0.028
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Double casement profile hook set 					-	486335	13373700	0.057	pcs	1	0.057
HS120	HS200	HS270	HS420	S270							
●	●	●	●	●							
Double casement profile hook set with microventilation 					-	486336	13373800	0.061	pcs	1	0.061
HS120	HS200	HS270	HS420	S270							
●	●	●	●								





Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Bottom locking point 					-	186934	13272900	0.035	pcs	1	0.035
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Spacer support 7.5mm 					-	196433	13278000	0.009	pcs	1	0.009
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Handle fastening kit 					-	225496	13179700	0.010	pcs	1	0.010
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Fastening kit 					-	189490	13274100	0.037	pcs	1	0.037
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Fastening kit 					-	486313	13374100	0.103	pcs	1	0.103
HS120	HS200	HS270	HS420	S270							
●	●	●	●	●							
Stop 					RAL 9016 RAL 9005 RAL 9006	187480	13173621 13173632 13276200	0.078	pcs	1	0.078
HS120	HS200	HS270	HS420	S270							
●	●	●	●	●							
Comfort Close mechanism ≤ 200 kg 					RAL 9005	304388	13374232	0.658	pcs	1	0.658
HS120	HS200	HS270	HS420	S270							
●	●										





Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Comfort Close mechanism 200-300 kg 					RAL 9006	304389	13374331	0.658	pcs	1	0.658
HS120	HS200	HS270	HS420	S270							
		●	●								
Mounting kit for Comfort Close mechanism 					-	485598	13374400	0.111	pcs	1	0.111
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Mounting kit for Comfort Close Slim Line mechanism 					-	486334	13374500	0.055	pcs	1	0.055
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Bracket for Comfort Close mechanism 					-	AYPC SL130.1706	13657400	0.047	pcs	1	0.050
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Locking bolt for Comfort Close mechanism 					-	305134	13278500	0.090	pcs	1	0.090
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Decorative cover plate 					RAL 9006	304816	13274931	0.003	pcs	1	0.003
HS120	HS200	HS270	HS420	S270							
●	●	●	●								
Microlift <200 kg 					-	239654	13171800	0.082	pcs	1	0.082
HS120	HS200	HS270	HS420	S270							
	●										





Name, drawing					Colour	Article	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Microlift >200 kg 					-	239657	13173100	0.089	pcs	1	0.089
HS120	HS200	HS270	HS420	S270							
		●	●								
Gas lift 					-	247164	13174700	0.097	pcs	1	0.097
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Cylinder 40/10 					-	DBCY-40/10	13105600	0.16	pcs	1	0.17
HS120	HS200	HS270	HS420	S270							
				●							
Cylinder 40/40 					-	DBCY-40/40	13105200	0.25	pcs	1	0.26
HS120	HS200	HS270	HS420	S270							
				●							
Cylinder 45/10 					-	5304.00	13118600	0.254	pcs	1	0.3
HS120	HS200	HS270	HS420	S270							
	●	●	●								
Cylinder 45/45 					-	5066.00	13117600	0.15	pcs	1	0.16
HS120	HS200	HS270	HS420	S270							
	●	●	●								



Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Universal punching tool 2990021 	-	18516000	137.0	pcs	1	146.0
Cassette tool 4110026 	-	18558600	4.5	pcs	1	5.0
Cassette tool 4110027 	-	18558700	4.5	pcs	1	5.0
Cassette tool 4110028 	-	18558800	5.0	pcs	1	5.5

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
<p>Cassette tool 4110029</p> 	-	18558900	5.5	pcs	1	6.0
<p>Cassette tool 4110030</p> 	-	18559000	5.5	pcs	1	6.0
<p>Cassette tool 4110031</p> 	-	18559100	7.5	pcs	1	8.0
<p>Cassette tool 4110032</p> 	-	18559200	10.0	pcs	1	10.5

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Cassette tool 4110033 	-	18559300	10.0	pcs	1	10.5
Cassette tool 4110034 	-	18559400	11.5	pcs	1	12.0
Cassette tool 4110035 	-	18559500	11.5	pcs	1	12.0
Cassette tool 4110037 	-	18559600	12.5	pcs	1	13.0

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
<p>Cassette tool 4.110038</p> 	-	18559700	7.5	pcs	1	8.0
<p>Cassette tool 4.110039</p> 	-	18559800	10.0	pcs	1	10.5
<p>Cassette tool 4.110040</p> 	-	18559900	8.0	pcs	1	8.5
<p>Cassette tool 4.110041</p> 	-	18560000	11.5	pcs	1	12.0

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
Cassette tool 4110042 	-	18560100	9.0	pcs	1	9.5
Jig AYPC.SL130.1980 	-	18541200	0.23	pcs	1	0.4
Jig AYPC.SL130.1981 	-	18541300	0.23	pcs	1	0.4
Jig AYPC.SL130.1982 	-	18541400	0.47	pcs	1	0.6

Name, article, drawing	Colour	Code	Weight, kg	Measure unit	Quantity in pack	Gross pack weight, kg
<p>Jig AYPC.SL130.1983</p> 	-	1854.1500	0.23	pcs	1	0.4
<p>Jig AYPC.SL130.1984</p> 	-	1854.1600	0.25	pcs	1	0.4

Article, Product name, Drawing	Colour	Code	Weight, kg	Volume, ml	Unit	Quantity in pack	Gross pack weight, kg	Application
One-component adhesive COSMO PU-100.130/0.31 	-	18609100	0.470	310 ml	pcs	1	0.560	Filling of corner connections of aluminium profiles, applied through cleats. The adhesive cures by reacting with moisture in the air.
Two-component adhesive COSMO PU-200.280/0.62 	-	18609200	0.900	2x310 ml	pcs	1	1.050	Filling of corner connections of aluminium profiles, applied through cleats. The adhesive cures by chemical reaction of components.
Manual mechanical dispensing gun COSMO SP-760.151 	-	18605200	1.380	-	pcs	1	1.780	Dosing of two-component adhesive COSMO PU-200.280
Cap COSMO SP-800.230 	-	18605300	0.011	-	pcs	1	0.013	For two-component adhesive COSMO PU-200.280
Surface cleaner COSMO CL-300.150/1 	-	18609300	0.710	1000 ml	pcs	1	0.736	Removal of PU glues from the painted profile surfaces (in the corner joint after crimping and fixing with dowels), removal of silicone from gaskets, cleaning of sealed surfaces.
Surface activator COSMO CL-310.110/0.25 	-	18609400	0.200	250 ml	pcs	1	0.278	Surface priming (PVC profiles, paint coated aluminium, etc.) before application of COSMO HD-100.412 (black) sealant. Improves adhesion on substrates difficult to bond (oil-based plastics, polyamide, smooth paints, etc.)

Article, Product name, Drawing	Colour	Code	Weight, kg	Volume, ml	Unit	Quantity in pack	Gross pack weight, kg	Application
Anti-corrosion sealant COSMO HD-100.411/0.31 	Grey	18609500	0.440	310 ml	pcs	1	0.525	Protection of aluminium profile edges against crevice corrosion. Acts as a sealant and prevents water seeping inside the profile through the joint.
Rubber sealant COSMO HD-100.412/0.31 	Black	18609800	0.440	310 ml	pcs	1	0.525	Bonding of rubber gaskets, sealing of profile joints, of drip drain and plug joints, etc. On painted profiles, apply COSMO CL-310.110 before the sealant.
Cyanoacrylate glue CA-500.200/0.02 	-	18609600	0.020	20 ml	pcs	1	0.032	Fast bonding of EPDM rubber gaskets (PE bottle with an applicator)
Primer for bonding TPE rubber and plastics COSMO SP-840.110/0.05 	-	18609700	0.035	50 ml	pcs	1	0.107	Primer for surfaces that are difficult to bond.



Read the manufacturer's instructions before using chemicals.





**ALUTECH SL130**  
Patio systems

# MAIN PROFILE CHARACTERISTICS



Frame profile  
AYPC.SL130.0101





		Article	
		3,9x25-A2ISO14585	100
		AYPC.SL130.0981	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0947	4 4 6
		AYPC.SL130.0953	2

Note:

\* Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0101	2.74	1084.29	20.2	8.90	22.7	116.9	17.98	65

Frame profile  
AYPC.SL130.0102




		Article	
		AYPC.W50.0929-01	80
		5x10DIN6325D	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0946	4 4 6
		AYPC.SL130.0953	2

Note:

\* Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0102	2.64	1033.29	20.0	8.85	22.6	108.7	16.72	65

Frame profile  
AYPC.SL130.0103




		Article	
		3.9x25-A2ISO14585	100
		AYPC.SL130.0982, AYPC.SL130.0982-01	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0945	4 4 6
		AYPC.SL130.0953, AYPC.SL130.0954	2 2

Note:  
\*Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0103	2.68	1091.93	14.7	5.39	27.29	107.2	15.55	68.95

Frame profile  
AYPC.SL130.0104




		Article	
		AYPC.SL130.0952	14
		AYPC.W50.0929-01	80
		5x10DIN6325D	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0945	4 4 4
		AYPC.SL130.0953, AYPC.SL130.0954	2 2

Note:

\*Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0104	2.56	1047.35	14.5	5.31	27.33	100.2	14.57	68.79



Frame profile  
AYPC.SL130.0105



		Article	
		AYPC.SL130.0947	20


Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0105	2.49	1030.05	118	4.51	26.19	100.4	14.66	68.48

Frame profile  
AYPC.SL130.0106




		Article	
		AYPC.SL130.094.7	20

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0106	2.48	1060.59	16.1	7.04	22.88	109.5	16.85	65



Frame profile  
AYPC.SL130.0107




		Article	
		3.9x25-A2ISO14585	100
		AYPC.SL130.0983, AYPC.SL130.0983-01	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0945, AYPC.SL130.0946	4 4 4 6
		AYPC.SL130.0953,	2
		AYPC.SL130.0954,	2
		AYPC.SL130.0955	2

Note:


\*Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0107	4.04	1611.17	24.6	9.71	25.33	369.8	35.14	105.25



Frame profile  
AYPC.SL130.0108

1 : 2




		Article	
		AYPC.SL130.0952	14
		AYPC.SL130.0952-01	51
		AYPC.SL130.0952-02	17
		AYPC.W50.0929-01	51
		5x10DIN6325D	100
		* AYPC.SL130.0943, AYPC.SL130.0944, AYPC.SL130.0945, AYPC.SL130.0946	4 4 4 6
		AYPC.SL130.0953,	2
		AYPC.SL130.0954,	2
		AYPC.SL130.0955	2


Note:

\*Can be installed only on the side of the bottom horizontal frame.

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0108	3.85	1539.38	24.3	9.61	25.28	346.6	32.86	105.49




Frame profile  
AYPC.SL130.0109



		Article	
		AYPC.SL130.0947	20



Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0109	3.49	1412.96	19.4	7.92	24.51	338.9	32.13	105.47



		Article	
		AYPC.SL130.0951	96
		5x10DIN6325D	100
		AYPC.W62.0912	120
		AYPC.SL130.0918	120
		AYPC.SL130.0950-02	65
		AYPC.SL130.0947	20
		AYPC.SL130.0950-02	65
		AYPC.W62.0913, AYPC.W62.0914	120
		AYPC.SL130.0947	20


Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0201	183	749.77	23.6	5.05	46.75	27.7	7.43	37.26

Sash profile  
AYPC.SL130.0202




		Article	
		AYPC.SL130.0950	130
		AYPC.SL130.0946	20

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0202	1.09	480.63	3.7	1.21	30.57	12.1	3.77	32.09





Sash profile  
AYPC.SL130.0203



		Article	
		AYPC.SL130.0950	130
		AYPC.SL130.0946	20


Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0203	2.01	818.13	8.6	2.58	33.34	77.5	13.32	58.18

Sash profile  
AYPC.SL130.0204




		Article	
		AYPC.SL130.0950	65
		AYPC.SL130.0946	20

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0204	2.01	817.01	86	2.58	33.34	67.5	1100	6136




Sash profile  
AYPC.SL130.0205




		Article	
		AYPC.SL130.0951	96
		5x10DIN6325D	100
		AYPC.W62.0912	120

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0205	2.09	803.14	212	6.93	30.61	313	6.41	48.80




Transom profile  
AYPC.SL130.0301




		Article	
		AYPC.SL130.0950-01	130
		AYPC.SL130.0946	20
		AYPC.W62.0913, AYPC.W62.0914	120, 20

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0301	129	532.23	8.4	2.37	35.5	14.6	4.28	34.08





Adapter  
AYPC.SL130.0502



		Article	
			
			
			
			
			
			
			
			
			
			
			
		3.9x13-A2ISO14585	100


Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0502	184	725.97	4.6	3.03	15.19	76.6	11.23	68.19

Adapter  
AYPC.SL130.0503




		Article	
		AYPC.W62.0957	200
		3.9x13-A2ISO14585	100
		3.9x13-A2ISO14585	100

Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0503	1.89	736.98	7.65	3.26	23.44	89.06	1196	74.45




Reinforcing profile  
AYPC.SL130.0702




		Article	
		3.9x19-A2ISO14586	100


Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0702	1.18	482.29	1.9	138	13.76	8.7	363	24




Corner crimping profile  
AYPC.SL160.0702




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL160.0202	157	583.0	112	5.60	20	49.4	1133	43.6



Corner crimping profile  
AYPC.SL160.0705




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL160.0705	0.99	368.56	34	4.91	28.6	14.0	10.00	14




AYPC.SL130.0201 sash profile assembled with  
AYPC.SL160.0702, AYPC.SL130.0702 reinforcing profile


AYPC.SL130.0201 + AYPC.SL160.0702




AYPC.SL130.0201 + AYPC.SL160.0702+ AYPC.SL130.0702




AYPC.SL130.0201 + AYPC.SL160.0702\*




AYPC.SL130.0201 + AYPC.SL160.0702\*+ AYPC.SL130.0702




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0201+ AYPC.SL160.0702	3.40	1200.57	184.9	24.77	74.64	43.4	9.32	46.55
AYPC.SL130.0201+ AYPC.SL160.0702+ AYPC.SL130.0702	4.58	1682.86	220.0	26.49	83.06	64.3	12.69	50.66
AYPC.SL130.0201+ AYPC.SL160.0702*	3.40	1200.57	173.5	23.82	72.85	42.8	9.27	46.15
AYPC.SL130.0201+ AYPC.SL160.0702*+ AYPC.SL130.0702	4.58	1682.86	211.4	25.87	81.71	61.3	11.80	51.93



AYPC.SL130.0201 sash profile assembled with  
AYPC.SL160.0705, AYPC.SL130.0702 reinforcing profile




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0201+ AYPC.SL160.0705	2.78	986.14	88.0	13.88	63.39	32.3	6.98	46.29
AYPC.SL130.0201+ AYPC.SL160.0705+ AYPC.SL130.0702	3.96	1468.43	107.7	15.43	69.79	49.8	9.41	52.95
AYPC.SL130.0201+ AYPC.SL160.0705*	2.78	986.14	95.0	14.49	65.58	32.1	6.83	47.03
AYPC.SL130.0201+ AYPC.SL160.0705*+ AYPC.SL130.0702	3.96	1468.43	112.7	15.79	71.36	49.8	9.41	52.95
AYPC.SL130.0201+ AYPC.SL130.0702	3.01	1232.06	32.7	10.87	30.07	42.4	7.62	55.67




AYPC.SL130.0205 sash profile assembled with  
AYPC.SL160.0702, AYPC.SL160.0705 reinforcing profile


AYPC.SL130.0205 + AYPC.SL160.0702




AYPC.SL130.0205 + AYPC.SL160.0702\*




AYPC.SL130.0202 + AYPC.SL160.0705



AYPC.SL130.0202 + AYPC.SL160.0705\*




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0205+ AYPC.SL160.0702	3.08	1253.85	187.0	24.57	76.10	46.3	952	48.66
AYPC.SL130.0205+ AYPC.SL160.0702*			176.1	23.67	74.39	46.3	952	48.66
AYPC.SL130.0202+ AYPC.SL160.0705	2.08	717.0	8.9	2.67	33.39	72.0	10.86	66.27
AYPC.SL130.0202+ AYPC.SL160.0705*			8.8	2.64	33.39	62.4	10.39	60.08




AYPC.SL130.0301 sash profile assembled with AYPC.SL160.0702,  
AYPC.SL160.0705 reinforcing profile


AYPC.SL130.0301 + AYPC.SL160.0705




AYPC.SL130.0301 + AYPC.SL160.0705\*



AYPC.SL130.0301 + AYPC.SL160.0705+ AYPC.SL160.0705\*



AYPC.SL130.0301 + AYPC.SL160.0702




Profile	m, kg/m	S, mm <sup>2</sup>	Jx, cm <sup>4</sup>	Wx, cm <sup>3</sup>	ay, mm	Jy, cm <sup>4</sup>	Wy, cm <sup>3</sup>	ax, mm
AYPC.SL130.0301+ AYPC.SL160.0705	2.28	791.82	65.8	11.25	58.51	12.9	3.63	35.5
AYPC.SL130.0301+ AYPC.SL160.0705*			83.1	13.42	61.92	12.9	3.63	35.5
AYPC.SL130.0301+ AYPC.SL160.0705+ AYPC.SL160.0705	3.27	1160.55	219.3	24.96	87.85	17.5	4.93	35.5
AYPC.SL130.0301+ AYPC.SL160.0702	2.86	1006.14	135.5	18.51	73.20	23.4	6.59	35.5



**ALUTECH SL130**  
Patio systems

# TABLE OF GLAZING






Note:  
Data given in the table is for reference only, the values are suitable for preliminary calculation. In common use, it is necessary to check their validity on the basis of actual parameters, such as accuracy of infill unit manufacturing (tolerance), accuracy of gasket manufacturing (tolerance), conditions of gasket installation and system assemblage, tolerances for glass bead profile and tolerances for assemblage of the combined profile.  
For correct system operation the gaskets must be tightened.

Infill unit thickness, mm	External gasket	Internal gasket					Glass beads		
	FRK29-01	FRK191	FRK192	FRK193	FRK194	Glass beads with polymer coating	Glass beads with anodic coating	Burglar resistant glass beads	
24	•	•	•	•	•		X	X	
26	•	•	•	•	•				
28	•	•	•	•	•		X	X	
30	•	•	•	•	•				
32	•	•	•	•	•		X	X	
34	•	•	•	•	•				
36	•	•	•	•	•		X	X	
38	•	•	•	•	•				
40	•	•	•	•	•		X	X	
42	•	•	•	•	•				

Application table of bearing and leveling supports for infill

Profile system	Infill unit thickness, mm	Bearing support	Leveling support
	24-26	AYPC.W62.0901M or AYPC.SL130.0906	100x32x3
	28-34		100x38x3
	36-38		100x44x3
	40-42		100x50x3
	24-26	-	100x22x2(5) 100x32x3
	28-34		100x22x2(5) 100x38x3
	36-38		100x22x5 100x32x2 100x44x3
	40-42		100x22x5 100x32x2 100x50x3
	24-26	-	100x22x2 100x32x3
	28-34		100x22x2 100x38x3
	36-38		100x32x2 100x44x3
	40-42		100x32x2 100x50x3





ALT SL130 series door unit installation in facade using AYPEC.SL130.0503 adapter profile		2nd level transom, overlap milling					
Mullion		2nd level transom, overlap milling					
		Frame profile	Self-tapping screw				
		Auxiliary transom profile	on mullion, step 450 mm	on mullion, step 600 mm	on transom, step 600 mm		
		Auxiliary mullion profile	E	H	I	J	K
		Min transom profile	D				
		Min mullion profile	C				
		Frame profile	B				
		Infill unit thickness					
		22 mm		3,9x19-A2IS014-586	3,9x13-A2IS014-586	4,8x60-A2IS014-586	4,8x60-A2IS014-586
		24 mm		AYPEC.F50.0701	AYPEC.F50.0701	AYPEC.F50.0701	AYPEC.F50.0701
		26 mm		AYPEC.F50.0701	AYPEC.F50.0701	AYPEC.F50.0701	AYPEC.F50.0701
		28 mm		AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702
		30 mm		AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702
		32 mm		AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702	AYPEC.F50.0702
34 mm		AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703		
36 mm		AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703		
38 mm		AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703	AYPEC.F50.0703		
40 mm		AYPEC.F50.0704	AYPEC.F50.0704	AYPEC.F50.0704	AYPEC.F50.0704		
42 mm		AYPEC.F50.0704	AYPEC.F50.0704	AYPEC.F50.0704	AYPEC.F50.0704		



Data on AYPEC.F50.0701, AYPEC.F50.0702, AYPEC.F50.0703 and AYPEC.F50.0704 auxiliary profiles is provided in ALT F50 technical manual.



**ALUTECH SL130**  
Patio systems

# SECTIONS AND JUNCTIONS

01

02

03

04

05

06


07

08


09




Typical door configurations. Frame profile fixing at 45°. External view



Typical door configurations. Frame profile fixing at 90°. External view




Typical door configurations. External view




Section	Page	Section	Page	Section	Page	Section	Page	Section	Page
1-1	06.05	18-18	06.17	37-37	06.27	56-56	06.38	75-75	06.47
2-2	06.05	19-19	06.17	38-38	06.28	57-57	06.38	76-76	06.48
3-3	06.06	20-20	06.18	39-39	06.28	58-58	06.39	77-77	06.48
4-4	06.06	21-21	06.19	40-40	06.29	59-59	06.39	78-78	06.49
5-5	06.07	22-22	06.19	41-41	06.29	60-60	06.40	79-79	06.49
6-6	06.08, 06.09, 06.10	23-23	06.20	42-42	06.30	61-61	06.40	80-80	06.50
7-7	06.11	24-24	06.20	43-43	06.30	62-62	06.41	81-81	06.50
8-8	06.11	25-25	06.21	44-44	06.31	63-63	06.41	82-82	06.51
9-9	06.12	26-26	06.21	45-45	06.32	64-64	06.42	83-83	06.51
10-10	06.12	27-27	06.22	46-46	06.33	65-65	06.42	84-84	06.52
11-11	06.13	28-28	06.22	47-47	06.33	66-66	06.43	85-85	06.52
12-12	06.13	29-29	06.23	48-48	06.34	67-67	06.43	86-86	06.53
13-13	06.14	30-30	06.23	49-49	06.34	68-68	06.44	87-87	06.54
14-14	06.15	31-31	06.24	50-50	06.35	69-69	06.44	88-88	06.55
15-15	06.15	32-32	06.25	51-51	06.35	70-70	06.45	89-89	06.56
16-16	06.16	33-33	06.25	52-52	06.36	71-71	06.45		
17-17	06.16	34-34	06.26	53-53	06.36	72-72	06.46		
		35-35	06.26	54-54	06.37	73-73	06.46		
		36-36	06.27	55-55	06.37	74-74	06.47		





Sections marked "XXа" are specular reflection of sections "XX".  
 Type A – doors with AYPC.SL130.0101 or AYPC.SL130.0102 frame.  
 Type C – doors with AYPC.SL160.0103 or AYPC.SL130.0104 frame.  
 Type D – doors with AYPC.SL160.0107 or AYPC.SL130.0108 frame.






SL130 HS






SL130 S





Scale 1:2






Scale 1:2





Scale 1:2




Scale 1:2




Scale 1:2




6c-6c




6d-6d






6e-6e


Scale 1:2







6f-6f




6g-6g




Scale 1:2




Scale 1:2




9-9




10-10




Scale 1:2




12a-12a




12-12




Scale 1:2




13-13




13a-13a




Scale 1:2




14-14




15-15




Scale 1:2




16-16




17-17




18-18




Scale 1:2





19a-19a




19b-19b




Scale 1:2




Scale 1:2




21-21




22-22




Scale 1:2




23-23




24-24




Scale 1:2




25-25




26-26







Scale 1:2

27-27




28-28






Scale 1:2


29-29




30-30




Scale 1:2




31a-31a




31b-31b




Scale 1:2




32-32




33-33






Scale 1:2


34-34




35-35




Scale 1:2




36-36




37-37






Scale 1:2


38-38




39-39




Scale 1:2




40-40





41-41







Scale 1:2




Scale 1:2



44a-44a





44b-44b





45a-45a

Scale 1:2





45b-45b







Scale 1:2




Scale 1:2




48-48




49-49




Scale 1:2




50-50




51-51




Scale 1:2






**52-52**




**53-53**




Scale 1:2




Scale 1:2




56-56




57-57




Scale 1:2




58-58




59-59




Scale 1:2




60-60




61-61




Scale 1:2




62-62




63-63




Scale 1:2




64-64




65-65




Scale 1:2




66-66




67-67




Scale 1:2




68-68




69-69







Scale 1:2

70-70




71-71






Scale 1:2


72-72




73-73




Scale 1:2




74-74




75-75




Scale 1:2




76-76




77-77




Scale 1:2




78-78




79-79




Scale 1:2




80-80




81-81




Scale 1:2




82-82




83-83






84-84


Scale 1:2




85-85




Scale 1:2




86a-86a




86b-86b






87a-87a


Scale 1:2




87b-87b




Scale 1:2




88a-88a




88b-88b




88c-88c



Scale 1:2



89-89







**ALUTECH SL130**  
Patio systems

# CALCULATION EXAMPLES





















Vertical sections



Horizontal sections



Article	Drawing		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
				1...		1...		1...
Profile								
AYPC.SL130.0102			L	2	L	2	L	2
			H	2	H	2	H	2
AYPC.SL130.0201			$L1=L/2+5$	4	$L1=L/3+30.7$	6	$L1=L/4+26.5$	8
			$H1=H-73$	4	$H1=H-73$	6	$H1=H-73$	7
AYPC.SL130.0205			-	-	-	-	$H2=H-73$	1
AYPC.SL130.0601			$L2=L1-138$	4	$L2=L1-138$	6	$L2=L1-138$	8
			$H3=H1-182$	4	$H3=H1-182$	6	$H3=H1-182$	8
AYPC.SL130.0801			$H4=H1$	2	$H4=H1$	4	$H4=H1$	4
AYPC.SL130.0805			$L3=L1-105$	1	$L3=L1-105$	2	$L3=2 \times L1-202$	1
AYPC.SL130.0805-01			$H5=H-59$	2	$H5=H-59$	2	$H5=H-59$	2
AYPC.SL130.0807			$L4=L-5$	3	$L4=L-5$	3	$L4=L-5$	3
AYPC.SL130.1901			$L5=L1-57$	1	$L5=L1-57$	2	$L5=L1-57$	2
			$H6=H1-55^*$	1	$H6=H1-55^*$	2	$H6=H1-55^*$	2
AYPC.SL130.1902			$H7=H1-10$	2	$H7=H1-10$	4	$H7=H1-10$	4
AYPC.SL130.1905			$L6=L-36^{**}$	2	$L6=L-36^{**}$	2	$L6=L-36^{**}$	2
			$H8=H-46$	2	$H8=H-46$	2	$H8=H-46$	2
AYPC.SL160.1950			$L7=L-92$	1	$L7=L-92$	1	$L7=L-94$	1

Article	Drawing	1..					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0940HS							
		2	1	4	2	4	2
AYPC.SL130.0940S							
		-	1	-	2	-	2
AYPC.SL130.0941HS		1	-	2	-	2	-
AYPC.SL130.0986		-	2	-	4	-	4
AYPC.W50.0929-01		8	8	8	8	8	8
AYPC.SL130.0951		16	16	24	24	32	32
AYPC.SL130.0905		5	5	2	2	10	10
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0907		1	1	2	2	2	2
AYPC.SL130.0908		3	3	3	3	3	3
AYPC.W62.0912		8	8	12	12	16	16
AYPC.SL130.0918		16	16	24	24	28	28
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL160.0928		H7/150+5	H7/150+5	H7/75+2	H7/75+2	H7/75+10	H7/75+10
AYPC.SL130.0943		4	4	4	4	4	4
AYPC.SL130.0944		4	4	4	4	4	4
AYPC.SL130.0947		1	1	1	1	1	1
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5	2xL1/500+5	2xL1/500+5
AYPC.W62.0901M		8	8	12	12	16	16
100x50x3		10	10	16	16	20	20
FRK170		8	8	12	12	16	16
FRK177		8	4	12	4	12	8
FRK178		4	2	6	2	6	4
FRK178-01		4	2	6	2	6	4


Article	Drawing	Type A1 Type A2				Type A5 Type A6				Type A7 Type A8			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1...		1...		1...		1...		1...		1...
Gaskets													
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	L1x2	1	L1x2	3	L1x2	1	L1x2	4	L1x2	2
FRK175		L1x2+H1x2	2	L1+H1x2	2	L1x3+H1x2	2	L1+H1x2	2	L1x4+H1x3	2	L1x2+H1x3	2
FRK188		2xL7+H1	1	2xL7+H1	1	2xL7+2xH1	1	2xL7+2xH1	1	L7	2	L7	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK230		H7	2	H7	2	H7	4	H7	4	H7	4	H7	4
ISE01		L3+H5x2+H7x2	1	L3+H5x2+H7x2	1	L3+H5+H7x2	2	L3+H5+H7x2	2	L3+H5x2+H7x4	1	L3+H5x2+H7x4	1
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x2	4

Article	Drawing	1...		
		Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
Hardware				
3.9x9.5-A2ISO14585		H7/150	H7/75	H7/75
3.9x25-A2ISO14585		10	4	20
4.8x4.5-A2ISO14585		5	2	10
3.9x13-A2ISO14586		L4/100	L4/100	L4/100
5x10DIN6325D		48	64	76
5x14DIN6325D		-	-	4


Infill					
Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	3	A=L1-154; B=H1-154	4




1. When manufacturing types A5, A6 and A7, A8 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).
  2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 - Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 - 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2






















Horizontal sections. Variant 3



Horizontal sections. Variant 4



Article	Drawing		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8		
				1...		1...		1...	
Profile									
AYPC.SL130.0102		 	L	2	L	2	L	2	
			H	2	H	2	H	2	
AYPC.SL130.0201			L1=L/2-39	2	L1=L/3-5	2	L1=L/4-17.5	4	
			L2=L1	2	L2=L1	2	L2=L1	4	
			-	-	L3=L/3-74	2	-	-	
			H1=H-73	2	H1=H-73	2	H1=H-73	3	
Select	Variant 1								
	AYPC.SL130.0202			2		4		4	
	Variant 2								
	AYPC.SL130.0202			1		2		2	
	AYPC.SL130.0204			1		2		2	
	Variant 3			H2=H1-55		H2=H1-55		H2=H1-55	
	AYPC.SL130.0202			1		2		2	
	AYPC.SL130.0203			1		2		2	
	Variant 4								
AYPC.SL130.0203			1		2		2		
AYPC.SL130.0204			1		2		2		
AYPC.SL130.0205			-	-	-	-	H3=H-73	1	
AYPC.SL130.0601			L4=L1-69	4	L4=L1-69	6	L4=L1-69	8	
			H4=H1-182	4	H4=H1-182	6	H4=H1-182	8	
AYPC.SL130.0802			H5=H1	2	H5=H1	4	H5=H1	4	
AYPC.SL130.0805			L5=L1-36	1	L5=L1-36	2	L5=2xL1-64	1	
AYPC.SL130.0805-01			H6=H-59	2	H6=H-59	2	H6=H-59	2	
AYPC.SL130.0807			L6=L-5	3	L6=L-5	3	L6=L-5	3	
AYPC.SL130.1901			L7=L1-27.5	1	L7=L1-27.5	2	L7=L1-27.5	2	
			H7=H1-55*	1	H7=H1-55*	2	H7=H1-55*	2	
AYPC.SL130.1903			H8=H1-10	2	H8=H1-10	4	H8=H1-10	4	
AYPC.SL130.1905			L8=L-36**	2	L8=L-36**	2	L8=L-36**	2	
			H9=H-46	2	H9=H-46	2	H9=H-46	2	
AYPC.SL160.1950			L9=L-92	1	L9=L-90	1	L9=L-94	1	

Article	Drawing	1..					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.094.0HS-01		2	1	4	2	4	2
AYPC.SL130.094.0S-01		-	1	-	2	-	2
AYPC.SL130.094.1HS-01		1	-	2	-	2	-
AYPC.SL130.0985		-	2	-	4	-	4
AYPC.W50.0929-01		8	8	8	8	8	8
AYPC.SL130.0950-02		8	8	16	16	16	16
AYPC.SL130.0951		8	8	8	8	16	16
AYPC.SL130.0905		5	5	2	2	10	10
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0907		1	1	2	2	2	2
AYPC.SL130.0908		3	3	3	3	3	3
AYPC.W62.0912		4	4	4	4	8	8
AYPC.SL130.0913		4	4	8	8	8	8
AYPC.SL130.0918		8	8	8	8	12	12
AYPC.SL130.0925		N***	N***	N***	N***	N***	N***
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL160.0928		5	5	2	2	10	10
AYPC.SL130.0943		4	4	4	4	4	4
AYPC.SL130.0944		4	4	4	4	4	4
AYPC.SL130.0947		2	2	2	2	2	2

Article	Drawing	1...					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5	2xL1/500+5	2xL1/500+5
AYPC.W62.0901M		8	8	12	12	16	16
100x50x3		10	10	16	16	20	20
FRK170		8	8	12	12	16	16
FRK177		8	4	12	4	12	8
FRK178		4	2	6	2	6	4
FRK178-01		4	2	6	2	6	4

Article	Drawing	Type A1 Type A2				Type A5 Type A6				Type A7 Type A8			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
		L	1..	L	1..	L	1..	L	1..	L	1..	L	1..
Gaskets													
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	L1x2	1	L1x2	3	L1x2	1	L1x2	4	L1x2	2
FRK175		L1x2+H1x2	2	L1+H1x2	2	L1x3+H1x2	2	L1+H1x2	2	L1x4+H1x3	2	L1x2+H1x3	2
FRK188		2xL9+H1	1	2xL9+H1	1	2xL9+2xH1	1	2xL9+2xH1	1	L9	2	L9	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK230		H8	2	H8	2	H8	4	H8	4	H8	4	H8	4
ISE01		L5+H6x2	1	L5+H6x2	1	L5+H6	2	L5+H6	2	L5+H6x2	1	L5+H6x2	1
IS10		H8	2	H8	2	H8	4	H8	4	H8	4	H8	4
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x2	4


Article	Drawing	1...		
		Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
Hardware				
3.9x25-A2ISO14585		10	4	20
4.8x45-A2ISO14585		5	2	10
3.9x13-A2ISO14586		L6/100	L6/100	L6/100
3.9x19-A2ISO14586		H8/150	H8/75	H8/75
5x10DIN6325D		32	32	44
5x14DIN6325D		-	-	4

Variant	AYPC.SL130.0925 quantity, N, pcs		
	Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
1	-	-	-
2	2	4	4
3	2	4	4
4	4	8	8

Infill			
Type A1 Type A2	Type A5 Type A6	Type A7 Type A8	
A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	3
A=L1-85; B=H1-154	4	A=L1-85; B=H1-154	4


- When manufacturing types A5, A6 and A7, A8 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).
  - Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.  
 \*\*\*AYPC.SL130.0925 cover is used only with sash profile AYPC.SL130.0203 or AYPC.SL130.0204 (see application table).






SL130 HS


SL130 S











Vertical sections







Horizontal sections



Article	Drawing		Type A3		Type A9 Type A10	
				1...		1...
Profile						
AYPC.SL130.0102			L	2	L	2
			H	2	H	2
AYPC.SL130.0201			L1=L/2+5	4	L1=L/4+26.5	8
			H1=H-73	4	H1=H-73	7
AYPC.SL130.0205			-	-	H2=H-73	1
AYPC.SL130.0601			L2=L1-138	4	L2=L1-138	8
			H3=H1-182	4	H3=H1-182	8
AYPC.SL130.0801			H4=H1	2	H4=H1	4
AYPC.SL130.0805-01			H5=H-59	2	H5=H-59	2
AYPC.SL130.0807			L3=L-5	3	L3=L-5	3
AYPC.SL130.1901			L4=L1-57	2	L4=L1-57	4
			H6=H1-55*	2	H6=H1-55*	4
AYPC.SL130.1902			H7=H1-10	2	H7=H1-10	4
AYPC.SL130.1905			L5=L-36**	2	L5=L-36**	2
			H8=H-46	2	H8=H-46	2
AYPC.SL130.1950			L6=L-92	2	L6=L-94	2

Article	Drawing	1...			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.094.0HS		2	-	4	-
AYPC.SL130.094.0S		-	2	-	4
AYPC.SL130.094.1HS		1	-	2	-
AYPC.SL130.0986		-	2	-	4
AYPC.W50.0929-01		8	8	8	8
AYPC.SL130.0951		16	16	32	32
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0907		1	1	2	2
AYPC.SL130.0908		3	3	3	3
AYPC.W62.0912		8	8	16	16
AYPC.SL130.0918		16	16	28	28
AYPC.SL130.0933K		-	-	2	2
AYPC.SL160.0928		H7/150	H7/150	H7/75	H7/75
AYPC.SL130.094.3		4	4	4	4
AYPC.SL130.094.4		4	4	4	4
AYPC.SL130.094.7		1	1	1	1
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5
AYPC.W62.0901M		8	8	16	16
100x50x3		12	12	24	24
FRK170		8	8	16	16
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-



Article	Drawing	Type A3				Type A9 Type A10			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..
Gaskets									
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	-	-	L1x2	4	-	-
FRK175		L1x2+H1x2	2	H1x2	2	L1x4+H1x3	2	H1x3	2
FRK188		L6+H1	2	L6+H1	2	L6+H1	2	L6+H1	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK230		H7	2	H7	2	H7	4	H7	4
ISE01		2xH7+2xH5	1	2xH7+2xH5	1	2xH7+H5	2	2xH7+H5	2
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8

Article	Drawing	1..	
		Type A3	Type A9 Type A10
Hardware			
3.9x9.5-A2ISO14585		H7/150	H7/75
3.9x13-A2ISO14586		L3/100	L3/100
5x10DIN6325D		48	76
5x14DIN6325D		-	4


Infill			
Type A3		Type A9 Type A10	
A=L1-154, B=H1-154	2	A=L1-154, B=H1-154	4




1. When manufacturing types A9 and A10 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).
  2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
\*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2









Horizontal sections. Variant 3







Horizontal sections. Variant 4



Article	Drawing		Type A3		Type A9 Type A10			
				1...		1...		
Profile								
AYPC.SL130.0102			L	2	L	2		
			H	2	H	2		
AYPC.SL130.0201			L1=L/2-39	2	L1=L/4-17.5	4		
			L2=L1	2	L2=L1	4		
			H1=H-73	2	H1=H-73	3		
Select	Variant 1			H2=H1-55	H2=H1-55			
	AYPC.SL130.0202						2	4
	Variant 2							
	AYPC.SL130.0202						1	2
	AYPC.SL130.0204						1	2
	Variant 3							
	AYPC.SL130.0202						1	2
	AYPC.SL130.0203						1	2
	Variant 4							
	AYPC.SL130.0203						1	2
AYPC.SL130.0204		1	2					
AYPC.SL130.0205			-	-	H3=H-73	1		
AYPC.SL130.0601			L3=L1-69	4	L3=L1-69	8		
			H4=H1-182	4	H4=H1-182	8		
AYPC.SL130.0802			H5=H1	2	H5=H1	4		
AYPC.SL130.0805-01			H6=H-59	2	H6=H-59	2		
AYPC.SL130.0807			L4=L-5	3	L4=L-5	3		
AYPC.SL130.1901			L5=L1-27.5	2	L5=L1-27.5	4		
			H7=H1-55*	2	H7=H1-55*	4		
AYPC.SL130.1903			H8=H1-10	2	H8=H1-10	4		
AYPC.SL130.1905			L6=L-36**	2	L6=L-36**	2		
			H9=H-46	2	H9=H-46	2		
AYPC.SL130.1950			L7=L-92	2	L7=L-94	2		

Article	Drawing	1..			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0940HS-01		2	-	4	-
AYPC.SL130.0940S-01		-	2	-	4
AYPC.SL130.0941HS-01		1	-	2	-
AYPC.SL130.0985		-	2	-	4
AYPC.W50.0929-01		8	8	8	8
AYPC.SL130.0950-02		8	8	16	16
AYPC.SL130.0951		8	8	16	16
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0907		1	1	2	2
AYPC.SL130.0908		3	3	3	3
AYPC.W62.0912		4	4	8	8
AYPC.W62.0913		4	4	8	8
AYPC.SL130.0918		8	8	12	12
AYPC.SL130.0925		N***	N***	N***	N***
AYPC.SL130.0933K		-	-	2	2
AYPC.SL130.0943		4	4	4	4
AYPC.SL130.0944		4	4	4	4
AYPC.SL130.0947		2	2	2	2
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5
AYPC.W62.0901M		8	8	16	16
100x50x3		12	12	24	24
FRK170		8	8	16	16

Article	Drawing	1..			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-

Article	Drawing	Type A3				Type A9 Type A10			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..
Gaskets									
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	-	-	L1x2	4	-	-
FRK175		L1x2+H1x2	2	H1x2	2	L1x4+H1x3	2	H1x3	2
FRK188		L7+H1	2	L7+H1	2	L7+H1	2	L7+H1	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK230		H8	2	H8	2	H8	4	H8	4
ISE01		H6	2	H6	2	H6	2	H6	2
IS10		H8	2	H8	2	H8	4	H8	4
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8


Article	Drawing	1..	
		Type A3	Type A9 Type A10
Hardware			
3.9x13-A2 ISO14586		L4/100	L4/100
3.9x19-A2ISO14586		H8/150	H8/75
5x10DIN6325D		32	44
5x14DIN6325D		-	4

Variant	AYPC.SL130.0925 quantity, N, pcs	
	Type A3	Type A9 Type A10
1	-	-
2	2	4
3	2	4
4	4	8


Infill			
Type A3		Type A9 Type A10	
A=L1-85, B=H1-154	2	A=L1-85, B=H1-154	4




1. When manufacturing types A9 and A10 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).
  2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 HS




SL130 S



Type C1




Type C3




Type C4

Vertical sections







































Horizontal sections





Infill					
Type C1		Type C3		Type C4	
A=L1-154; B=H1-154	1	A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	2
A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	2

Distance to transom insert axle, $L_0$		
Type C1	Type C3	Type C4
$L_0 = L/2 - 71.5$	$L_0 = L/3 + 2.5$	$L_0 = L/4 - 50$

Article	Drawing	Type C1		Type C3		Type C4				
			1...		1...		1...			
Profile										
AYPC.SL130.0104			L	2		L	2		L	2
			H	2		H	2		H	2
AYPC.SL130.0201			$L1=L/2+43,5$	2		$L1=L/3+30,5$	4		$L1=L/4+65$	4
			H1=H-73	2		H1=H-73	4		H1=H-73	3
			H2=H-56	1		H2=H-56	2		H2=H-56	2
AYPC.SL130.0205			-	-		-	-		H3=H-73	1
AYPC.SL130.0601			L2=L1-138	4		L2=L1-138	6		L2=L1-138	8
			H4=H1-182	2		H4=H1-182	4		H4=H1-182	4
			H5=H-100	2		H5=H-100	2		H5=H-100	4
AYPC.SL130.0611			H6=H5	1		-	-		H6=H5	2
			L3=L2-22	2		L3=L2-44	2		L3=L2-22	4
AYPC.SL130.0801			H7=H1	1		H7=H1	2		H7=H1	2
			H8=H-56	1		H8=H-56	2		H8=H-56	2
AYPC.SL130.0803			$L4=L/2-40$	2		$L4=L/3-53$	4		$L4=2 \times L1-196$	2
AYPC.SL130.0804			H9=H-92	1		H9=H-92	2		-	-
AYPC.SL130.0807			L5=L-5	2		L5=L-5	2		L5=L-5	2
AYPC.SL130.1901			L6=L1-57	1		L6=L1-57	2		L6=L1-57	2
			H10=H1-55*	1		H10=H1-55*	2		H10=H1-55*	2
AYPC.SL130.1902			H11=H1-10	1		H11=H1-10	2		H11=H1-10	2
			H12=H-72	1		H12=H-72	2		H12=H-72	2
AYPC.SL130.1904			L7=L-36**	2		L7=L-36**	2		L7=L-36**	2
			H13=H-46	2		H13=H-46	2		H13=H-46	2
AYPC.SL130.1906			$L8=L/2-30,5$	2		$L8=L/3-43,5$	4		$L8=L4+18$	2
			H14=H-72	1		H14=H-72	2		-	-
AYPC.SL160.1950			L9=L-90	1		L9=L-90	1		L9=L-90	1

Article	Drawing	1...					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.094.0HS		1	-	2	-	2	-
AYPC.SL130.094.0S		-	1	-	2	-	2
AYPC.SL130.094.2HS		1	-	2	-	2	-
AYPC.SL130.0986-01		-	2	-	4	-	4
AYPC.W50.0929-01		4	4	4	4	4	4
AYPC.SL130.0950-02		4	4	8	8	8	8
AYPC.SL130.0951		8	8	16	16	16	16
AYPC.SL130.0952		8	8	8	8	8	8
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0908		2	2	2	2	2	2
AYPC.W62.0912		4	4	8	8	8	8
AYPC.SL130.0918		8	8	16	16	12	12
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL130.0943		2	2	2	2	2	2
AYPC.SL130.0944		2	2	2	2	2	2
AYPC.SL130.0945		8	8	8	8	8	8
AYPC.SL130.0947		1	1	1	1	1	1
AYPC.SL160.0928		H11/150	H11/150	H11/75	H11/75	H11/75	H11/75
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5	2xL1/500+5	2xL1/500+5
100x22x5		6	6	4	4	12	12
100x32x2		3	3	2	2	6	6
AYPC.W62.0901M		5	5	10	10	10	10
100x50x3		13	13	18	18	26	26


Article	Drawing	1...					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
FRK170		8	8	12	12	16	16
FRK177		4	-	8	-	4	-
FRK178		2	-	4	-	2	-
FRK178-01		2	-	4	-	2	-

Article	Name Drawing	Type C1				Type C3				Type C4			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1...		1...		1...		1...		1...		1...
Gaskets													
FRK29-01		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK176		L1x2	1	-	-	L1x2	2	-	-	L1x2	2	-	-
FRK175		L1x2+H1x2	1	H1x2	1	L1x2+H1x2	2	H1x2	2	L1x2+H1	2	H1x2	1
FRK188		L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1
FRK191		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK230		H1	2	H1	2	H1	4	H1	4	H1	4	H1	4
ISE01		2xH12+H9+2xL4	1	2xH12+H9+2xL4	1	4xH12+2H9+4xL4	1	4xH12+2H9+4xL4	1	4xH12+2xL4	1	4xH12+2xL4	1
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x4	2


Article	Drawing	1...		
		Type C1	Type C3	Type C4
Hardware				
3.9x9.5-A2ISO14585		H11/150	H11/75	H11/75
3.9x13-A2ISO14586		L/150	L/150	L/150
3.9x19-A2ISO14586		L8/250+H14/500+L3/250+H6/500	L8/125+H14/250+L3/250	L8/250+H6/250+L3/250
5x10DIN6325D		40	56	52
5x14DIN6325D		-	-	4




- When manufacturing types C3 and C4 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).
  - Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 - Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 - 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1904 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 HS




SL130 S



Type C1




Type C3




Type C4


Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2























Horizontal sections. Variant 3










Horizontal sections. Variant 4



Article	Drawing		Type C1		Type C3		Type C4	
				1...		1...		1...
Profile								
AYPC.SL130.0104			L	2	L	2	L	2
			H	2	H	2	H	2
AYPC.SL130.0201			L1=L/2-0.5	1	L1=L/3-5	2	L1=L/4+21	2
			L1=L/2-0.5	1	L1=L/3-5	2	L1=L/4+21	2
			H1=H-73	1	H1=H-73	2	H1=H-73	1
Select	Variant 1							
	AYPC.SL130.0202							
			H2=H1-55	1	H2=H1-55	2	H2=H1-55	2
			H3=H-56	1	H3=H-56	2	H3=H-56	2
	Variant 2							
	AYPC.SL130.0202							
			H2=H1-55	1	H2=H1-55	2	H2=H1-55	2
	AYPC.SL130.0204							
			H3=H-56	1	H3=H-56	2	H3=H-56	2
	Variant 3							
AYPC.SL130.0203								
		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2	
AYPC.SL130.0202								
		H3=H-56	1	H3=H-56	2	H3=H-56	2	
Variant 4								
AYPC.SL130.0203								
		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2	
AYPC.SL130.0204								
		H3=H-56	1	H3=H-56	2	H3=H-56	2	
AYPC.SL130.0205			-	-	-	-	H4=H-73	1
AYPC.SL130.0601			L2=L1-69	4	L2=L1-69	6	L2=L1-69	8
			H5=H1-182	2	H5=H1-182	4	H5=H1-182	4
			H6=H-100	2	H6=H-100	2	H6=H-100	4
AYPC.SL130.0611			H7=H-100	1	-	-	H7=H-100	2
			L3=L2-22	2	L3=L2-44	2	L3=L2-22	4
AYPC.SL130.0802			H8=H1	1	H8=H1	2	H8=H1	2
			H9=H-56	1	H9=H-56	2	H9=H-56	2
AYPC.SL130.0803			L4=L/2-14.5	2	L4=L/3-19	4	L4=2xL1-58	2
AYPC.SL130.0804			H10=H-92	1	H10=H-92	2	-	-
AYPC.SL130.0807			L5=L-5	2	L5=L-5	2	L5=L-5	2
AYPC.SL130.1901			L6=L1-27.5	1	L6=L1-27.5	2	L6=L1-27.5	2
			H11=H1-55*	1	H11=H1-55*	2	H11=H1-55*	2

Article	Drawing		Type C1		Type C3		Type C4	
				1...		1...		1...
Profile								
AYPC.SL130.1903			H12=H1-10	1	H12=H1-10	2	H12=H1-10	2
			H13=H-72	1	H13=H-72	2	H13=H-72	2
AYPC.SL130.1904			L7=L-36**	2	L7=L-36**	2	L7=L-36**	2
			H14=H-46	2	H13=H-46	2	H13=H-46	2
AYPC.SL130.1906			L8=L/2-10.5	2	L8=L/3-15	4	L8=L/2-8	2
			H15=H-72	1	H14=H-72	2	-	-
AYPC.SL160.1950			L9=L-90	1	L9=L-90	1	L9=L-90	1

Article	Drawing	1...					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.094.0HS-01		1	-	2	-	2	-
							
							
							
							
AYPC.SL130.094.0S-01		-	1	-	2	-	2
							
							
							
							
AYPC.SL130.094.2HS-01		1	-	2	-	2	-
							
AYPC.SL130.0985-01		-	2	-	4	-	4
AYPC.W50.0929-01		4	4	4	4	4	4
AYPC.SL130.0950		4	4	8	8	8	8
AYPC.SL130.0950-02		4	4	8	8	8	8
AYPC.SL130.0951		4	4	8	8	8	8
AYPC.SL130.0952		8	8	8	8	8	8

Article	Drawing	1..					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0908		2	2	2	2	2	2
AYPC.W62.0912		2	2	4	4	4	4
AYPC.W62.0913		2	2	4	4	4	4
AYPC.SL130.0918		4	4	8	8	4	4
AYPC.SL130.0925		N***	N***	N***	N***	N***	N***
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL130.0943		2	2	2	2	2	2
AYPC.SL130.0944		2	2	2	2	2	2
AYPC.SL130.0945		8	8	8	8	8	8
AYPC.SL130.0947		2	2	2	2	2	2
AYPC.100P.1850		L1/500+3	L1/500+3	2xL1/500+5	2xL1/500+5	2xL1/500+5	2xL1/500+5
100x22x5		6	6	4	4	12	12
100x32x2		3	3	2	2	6	6
AYPC.W62.0901M		5	5	10	10	10	10
100x50x3		13	13	18	18	26	26
FRK170		8	8	12	12	16	16
FRK177		4	-	8	-	4	-
FRK178		2	-	4	-	2	-
FRK178-01		2	-	4	-	2	-

Article	Drawing	Type C1				Type C3				Type C4			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..		1..		1..
Gaskets													
FRK29-01		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK176		L1x2	1	-	-	L1x2	2	-	-	L1x2	2	-	-
FRK175		L1x2+H1x2	1	H1x2	1	L1x2+H1x2	2	H1x2	2	L1x2+H1	2	H1x2	1
FRK188		L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1	L9+H1x2	1
FRK191		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK230		H1	2	H1	2	H1	4	H1	4	H1	4	H1	4
ISE01		2xL4+H9	1	2xL4+H9	1	2xL4+H9	2	2xL4+H9	2	L4	2	L4	2
IS10		H12	2	H12	2	H12	4	H12	4	H12	4	H12	4
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x2	4

Article	Drawing	1..		
		Type C1	Type C3	Type C4
Hardware				
3.9x13-A2ISO14586		L/150	L/150	L/150
3.9x19-A2ISO14586		L8/250+H15/500+L3/250+ +H7/500+H13/150	L8/125+H15/250+L3/250+ +H13/75	L8/250+L3/125+H7/250+ +H13/75
5x10DIN6325D		32	40	36
5x14DIN6325D		-	-	4

Infill					
Type C1		Type C3		Type C4	
A=L1-85, B=H1-154	1	A=L1-85, B=H1-154	2	A=L1-85, B=H1-154	2
A=L1-85, B1=H-72	1	A=L1-85, B1=H-72	1	A=L1-85, B1=H-72	2

Variant	AYPC.SL130.0925 quantity, N, pcs		
	Type C1	Type C3	Type C4
1	-	-	-
2	2	4	4
3	4	8	8
4	4	8	8

The distance to transom insert axle, L <sub>0</sub>		
Type C1	Type C3	Type C4
L <sub>0</sub> = L/2-57.5	L <sub>0</sub> = L/3-3	L <sub>0</sub> = L/4-36

1. When manufacturing types C3 and C4 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).



2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 - Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 - 08.44 for profile dimensions and cutting.


\*\*The length of AYPC.SL130.1904 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.

\*\*\*AYPC.SL130.0925 cover is used only with sash profile AYPC.SL130.0203 or AYPC.SL130.0204 (see application table).









Vertical sections






Vertical sections




Article	Drawing		Type D1		Type D5	
				1...		1...
Profile						
AYPC.SL130.0108			L	2	L	2
			H	2	H	2
AYPC.SL130.0201			$L1=L/3+56.5$	4	$L1=L/6+70.5$	8
			$H1=H-73$	4	$H3=H-73$	7
			$H2=H-56$	1	$H2=H-56$	2
AYPC.SL130.0205			-	-	$H3=H-73$	1
AYPC.SL130.0601			$L2=L1-138$	6	$L2=L1-138$	12
			$H4=H1-182$	4	$H4=H1-182$	8
			$H5=H1-100$	2	$H5=H1-100$	4






Vertical sections




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.0611			H6=H5	1	H6=H5	2
			L3=L2-22	2	L3=L2-22	4
AYPC.SL130.0801			H7=H1	3	H7=H1	6
			H8=H-56	1	H8=H-56	2
AYPC.SL130.0803			L4=2xL/3-52.5	2	L4=2xL/3-77.5	2
			H9=H-92	1	-	-
AYPC.SL130.0805-01			H10=H-59	3	H10=H-59	4
AYPC.SL130.0807			L5=L-5	2	L5=L-5	2
AYPC.SL130.1901 for SL130 HS lift and slide option			L6=L1-57	2	L6=L1-57	4
		H11=H1-55**	2	H11=H1-55**	4	
		L6=L1-57	1	L6=L1-57	1	
		L6=L1-57	1	L6=L1-57	3	
		H11=H1-55**	1	H11=H1-55**	1	

Horizontal sections



Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.1902			H12=H1-10	3	H12=H1-10	6
			H13=H-72	1	H13=H-72	2
AYPC.SL130.1904			L7=L-36**	2	L7=L-36**	2
AYPC.SL130.1905			L8=L-36**	2	L8=L-36**	2
			H14=H-46	1	-	-
AYPC.SL130.1906			L9=2xL/3-435	2	L9=2xL/3-595	2
			H15=H-56	1	-	-
AYPC.SL130.1950			L10=L-92	1	L10=L-94	2
			L11=L-94	1	-	-

Horizontal sections



Article	Drawing	Type D1				Type D5			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
		L	1..	L	1..	L	1..	L	1..
Gaskets									
FRK29-01		(A+B)x2	3	(A+B)x2	3	(A+B)x2	6	(A+B)x2	6
FRK176		Lx2	2	-	-	Lx2	4	-	-
FRK175		L1x2+H1	2	H1x2	1	L1x4+H1	2	H1x2	1
FRK188		L10x2+H1	1	L10x2+H1	1	L10	2	L10	2
FRK191		(A+B)x2	3	(A+B)x2	3	(A+B)x2	6	(A+B)x2	6
FRK230		H13	4	H13	4	H13	8	H13	8
ISE01		L4+H10x2+H13x2	2	L4+H10x2+H13x2	2	L4+H10x2+H13x4	2	L4+H10x2+H13x4	2
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8

Article	Drawing	1...			
		Type D1		Type D5	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0940HS		3	-	6	-
AYPC.SL130.0940S		-	3	-	6
AYPC.SL130.0941HS		1	-	2	-
AYPC.SL130.0942HS		1	-	2	-
AYPC.SL130.0943		4	4	4	4
AYPC.SL130.0944		2	2	2	2
AYPC.SL130.0945		4	4	4	4
AYPC.SL130.0946		4	4	4	4
AYPC.SL130.0947		1	1	1	1
AYPC.SL130.0986		-	2	-	4
AYPC.SL130.0986-01		-	2	-	4
AYPC.W50.0929-01		4	4	4	4
AYPC.SL130.0950-02		4	4	8	8
AYPC.SL130.0951		16	16	32	32
AYPC.SL130.0952		4	4	4	4
AYPC.SL130.0952-01		4	4	4	4
AYPC.SL130.0952-02		4	4	4	4
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0908		2	2	2	2
AYPC.W62.0912		8	8	16	16
AYPC.SL130.0918		16	16	28	28

Article	Drawing	1...			
		Type D1		Type D5	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0933K		-	-	2	2
AYPC.SL160.0928		H13/75	H13/75	H13/37.5	H13/37.5
AYPC.100P.1850		2xL1/500+3	2xL1/500+3	4xL1/500+5	4xL1/500+5
100x22x5		6	6	12	12
100x32x2		3	3	6	6
AYPC.W62.0901M		9	9	18	18
100x50x3		19	19	38	38
FRK170		12	12	24	24
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-

Article	Drawing	1...	
		Type D1	Type D5
Hardware			
3.9x9.5-A2ISO14585		H13/75	H13/37.5
3.9x13-A2ISO14586		L5/150	L5/150
3.9x19-A2ISO14586		L9/250+H15/500+L3/250+H6/500	L9/250+H6/250+L3/125
5x10DIN6325D		56	84
5x14DIN6325D		-	4

Infill			
Type D1		Type D5	
A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	4
A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	2

Distance to transom insert axle, L <sub>0</sub>	
Type D1	Type D5
L <sub>0</sub> = L/3-58.5	L <sub>0</sub> = L/6-44




1. When manufacturing types D1 and D5 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.33).




2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 - Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 - 08.44 for profile dimensions and cutting.


\*\* The length of AYPC.SL130.1904 and AYPC.SL130.1905 profiles is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 S








Vertical sections











Vertical sections




Article	Drawing	 Profile	Type D1		Type D5		
			 L	1...	 L	1...	
AYPC.SL130.0108			L	2	L	2	
AYPC.SL130.0201			L1=L/3+20.5	1	L1=L/6+35	2	
			L1=L/3+20.5	1	L1=L/6+35	2	
			H1=H-73	1	H1=H-73	1	
			L2=L/3-48.5	2	L2=L/6-34	4	
Select	Variant 1						
	AYPC.SL130.0202			H2=H1-55	3	H2=H1-55	6
	Variant 2						
	AYPC.SL130.0202			H2=H1-55	2	H2=H1-55	4
	AYPC.SL130.0204			H2=H1-55	1	H2=H1-55	2
H3=H-56				1	H3=H-56	2	






Vertical sections




Article	Drawing		Type D1		Type D5		
				1...		1...	
Variant 3							
AYPC.SL130.0203			H2=H1-55	2	H2=H1-55	4	
AYPC.SL130.0202			H2=H1-55	1	H2=H1-55	2	
			H3=H-56	1	H3=H-56	2	
Variant 4							
AYPC.SL130.0203				H2=H1-55	2	H2=H1-55	4
AYPC.SL130.0204			H2=H1-55	1	H2=H1-55	2	
			H3=H-56	1	H3=H-56	2	
AYPC.SL130.0205			-	-	H4=H-73	1	




Horizontal sections. Variant 1




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.0601			L3=L1-69	4	L3=L1-69	8
			L4=L2	2	L4=L2	4
			H5=H1-182	4	H5=H1-182	8
			H6=H-100	2	H6=H-100	4
AYPC.SL130.0611			H7=H-100	1	H7=H-100	2
			L5=L3-22	2	L5=L3-22	4
AYPC.SL130.0802			H8=H-73	3	H8=H-73	6
			H9=H-56	1	H9=H-56	2
AYPC.SL130.0803			L6=2xL/3-35.5	2	L6=2xL/6-44	2
			H9=H-92	1	-	-
AYPC.SL130.0805-01			H10=H-59	3	H10=H-59	4
AYPC.SL130.0807			L7=L-5	2	L7=L-5	2

Horizontal sections. Variant 2




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.1901			L8=L1-27.5	1	L8=L1-27.5	1
			L9=L2	1	L9=L2	3
			H11=H1-55*	1	H11=H1-55*	1
AYPC.SL130.1903			H12=H1-10	3	H12=H1-10	6
			H13=H-72	1	H13=H-72	2
AYPC.SL130.1904			L10=L-36**	2	L10=L-36**	2
AYPC.SL130.1905			L11=L-36**	2	L11=L-36**	2
			H14=H-46	1	-	-
AYPC.SL130.1906			L12=2xL/3-31.7	2	L12=2xL/3-36	2
			H15=H-56	1	-	-
AYPC.SL130.1950			L13=L-92	1	L13=L-94	2
			L14=L-94	1	-	-

Horizontal sections. Variant 3



Article	Drawing	1..	
		Type D1	Type D5
Accessories			
AYPC.SL130.0940S-01		3	6
AYPC.SL130.0943		4	4
AYPC.SL130.0944		2	2
AYPC.SL130.0945		4	4
AYPC.SL130.0946		4	4
AYPC.SL130.0947		2	2

Horizontal sections. Variant 4



Article	Drawing	1..	
		Type D1	Type D5
Accessories			
AYPC.SL130.0985		2	4
AYPC.SL130.0985-01		2	4
AYPC.W50.0929-01		4	4
AYPC.SL130.0950		4	8
AYPC.SL130.0950-02		12	24
AYPC.SL130.0951		4	8
AYPC.SL130.0952		4	4
AYPC.SL130.0952-01		4	4
AYPC.SL130.0952-02		4	4

Article	Drawing	1...	
		Type D1	Type D5
Accessories			
AYPC.SL130.0906		8	16
AYPC.SL130.0908		2	2
AYPC.W62.0912		2	4
AYPC.W62.0913		6	12
AYPC.SL130.0918		4	4
AYPC.SL130.0925		N***	N***
AYPC.SL130.0933K		-	2
AYPC.100P.1850		2xL1/500+3	4xL1/500+5
100x22x5		6	12
AYPC.W62.0901M		9	18
100x50x3		19	38
100x32x2		3	6
FRK170		12	24

Article	Drawing	Type D1		Type D5	
			1...		1...
Gaskets					
FRK29-01		(A+B)x2	3	(A+B)x2	6
FRK175		H1x2	1	H1x2	1
FRK188		L13x2+H1	1	L13	2
FRK191		(A+B)x2	3	(A+B)x2	6
FRK230		H13	4	H13	8
ISE01		L6x2+H9+H10x3	1	L6+H10x2	2
IS10		H13	4	H13	8
AYPC.SL130.0912		L1x2	4	L1x2	8

Article	Drawing	1...	
		Type D1	Type D5
Hardware			
3.9x13-A2IS014586		L7/150	L7/150
3.9x19-A2IS014586		L5/250+L12/250+H7/500+H13/75+H15/500	L5/125+L12/250+H7/250+H13/37.5
5x10DIN6325D		32	36
5x14DIN6325D		-	4


Infill			
Type D1		Type D5	
A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	4
A=L1-85; B1=H-72	1	A=L1-85; B1=H-72	2

Distance to transom insert axle, $L_0$	
Type D1	Type D5
$L_0 = L/3-36$	$L_0 = L/6-22$


Variant	AYPC.SL130.0925 quantity, N, pcs	
	Type D1	Type D5
1	-	-
2	4	8
3	4	8
4	8	16

1. When manufacturing types D1 and D5 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.33).
  2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1904 and AYPC.SL130.1905 profiles is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.  
 \*\*\*AYPC.SL130.0925 cover is used only with sash profile AYPC.SL130.0203 or AYPC.SL130.0204 (see application table).


















Vertical sections




Horizontal sections



Article	Drawing		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
				1...		1...		1...
Profile								
AYPC.SL130.0101			L=Lef-56	2	L=Lef-56	2	L=Lef-56	2
AYPC.SL130.0106			H	2	H	2	H	2
AYPC.SL130.0201			L1=Lef/2+5	4	L1=Lef/3+30.7	6	L1=Lef/4+26.5	8
			H1=H-73	4	H1=H-73	6	H1=H-73	7
AYPC.SL130.0205			-	-	-	-	H2=H1	1
AYPC.SL130.0601			L2=L1-138	4	L2=L1-138	6	L2=L1-138	8
			H3=H1-182	4	H3=H1-182	6	H3=H1-182	8
AYPC.SL130.0801			H4=H1	2	H4=H1	4	H4=H1	4
AYPC.SL130.0805			L3=L1-105	1	L3=L1-105	2	L3=2xL1-202	1
AYPC.SL130.0805-01			H5=H-59	2	H5=H-59	2	H5=H-59	2
AYPC.SL130.0806			H6=H-90	1	H6=H-90	2	-	-
AYPC.SL130.0807			L4=Lef-5	3	L4=Lef-5	3	L4=Lef-5	3
AYPC.SL130.1901			L5=L1-57	1	L5=L1-57	2	L5=L1-57	2
			H7=H1-55*	1	H7=H1-55*	2	H7=H1-55*	2
AYPC.SL130.1902			H8=H1-10	2	H8=H1-10	4	H8=H1-10	4
AYPC.SL130.1905			L6=Lef-56**	2	L6=Lef-56**	2	L6=Lef-56**	2
AYPC.SL130.1950			L7=Lef-94	1	L7=Lef-94	1	L7=Lef-94	1

Article	Drawing	1...					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0940HS		2	1	4	2	4	2
AYPC.SL130.0940S		-	1	-	2	-	2
AYPC.SL130.0941HS		1	-	2	-	2	-
AYPC.SL130.0981		4	4	4	4	4	4
AYPC.SL130.0986		-	2	-	4	-	4
AYPC.SL130.0951		16	16	24	24	32	32
AYPC.SL130.0905		5	5	2	2	10	10
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0907		1	1	2	2	2	2
AYPC.SL130.0908		3	3	3	3	3	3
AYPC.W62.0912		8	8	12	12	16	16
AYPC.SL130.0918		16	16	24	24	28	28
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL160.0928		H8/150+5	H8/150+5	H8/75+2	H8/75+2	H8/75+10	H8/75+10
AYPC.SL130.0943		4	4	4	4	4	4
AYPC.SL130.0944		4	4	4	4	4	4
AYPC.SL130.0947		11	11	11	11	11	11
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500	LEF/500	LEF/500
AYPC.W62.0901M		8	8	12	12	16	16
100x50x3		10	10	16	16	20	20
FRK170		8	8	12	12	16	16
FRK177		8	4	12	4	12	8

Article	Drawing	1...					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
FRK178		4	2	6	2	6	4
FRK178-01		4	2	6	2	6	4


Article	Drawing	Type A1 Type A2				Type A5 Type A6				Type A7 Type A8			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1...		1...		1...		1...		1...		1...
Gaskets													
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	L1x2	1	L1x2	3	L1x2	1	L1x2	4	L1x2	2
FRK175		2xL1+H1x2	2	L1+H1x2	2	L1x3+H1x2	2	L1+H1x2	2	L1x4+H1x3	2	L1x2+H1x3	2
FRK188		2xL7	1	2xL7	1	2xL7	1	2xL7	1	L7	2	L7	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK230		H8	2	H8	2	H8	4	H8	4	H8	4	H8	4
ISE01		L3+H5x2+H8x2	1	L3+H5+H8x2	1	L3+H5+H8x2	2	L3+H5+H8x2	2	L3+H5x2+H8x4	1	L3+H5x2+H8x4	1
AYPC.SL130.0912		-	-	L1x4	1	-	-	L1x4	2	-	-	L1x2	4

Drawing	Drawing	1..		
		Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
Hardware				
3,9x9,5-A2IS014585		H8/150	H8/75	H8/75
3,9x25-A2IS014585		26	20	36
4,8x45-A2IS014585		5	2	10
3,9x13-A2IS014586		L4/100	L4/100	L4/100
5x10DIN6325D		32	48	60
5x14DIN6325D		-	-	4


Infill					
Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	3	A=L1-154; B=H1-154	4




- When manufacturing types A5, A6 and A7, A8 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).
  - Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2




























Horizontal sections. Variant 3



Horizontal sections. Variant 4



Article	Drawing		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8					
				1...		1...		1...				
Profile												
AYPC.SL130.0101			L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2				
AYPC.SL130.0106			H	2	H	2	H	2				
AYPC.SL130.0201			L1=L <sub>EF</sub> /2-39	2	L1=L <sub>EF</sub> /3-5	2	L1=L <sub>EF</sub> /4-17,5	4				
			L2=L1	2	L2=L1	2	L2=L1	4				
			-	-	L3=L <sub>EF</sub> /3-74	2	-	-				
			H1=H-73	2	H1=H-73	2	H1=H-73	3				
Select	Variant 1			2	H2=H1-55	H2=H1-55	H2=H1-55	4				
	AYPC.SL130.0202								4	4		
	Variant 2								1	2	2	2
	AYPC.SL130.0202											
	AYPC.SL130.0204								1	2	2	2
	Variant 3								1	2	2	2
	AYPC.SL130.0202											
	AYPC.SL130.0203								1	2	2	2
Variant 4		1	2	2	2							
AYPC.SL130.0203												
AYPC.SL130.0204		1	2	2	2							
AYPC.SL130.0205			-	-	-	-	H3=H-73	1				
AYPC.SL130.0601			L4=L1-69	4	L4=L1-69	6	L4=L1-93	8				
			H4=H1-182	4	H4=H1-182	6	H4=H1-182	8				
AYPC.SL130.0802			H5=H1	2	H5=H1	4	H5=H1	4				
AYPC.SL130.0805			L5=L1-36	1	L5=L1-36	2	L5=2*L1-64	1				
AYPC.SL130.0805-01			H6=H-59	2	H6=H-59	2	H6=H-59	2				
AYPC.SL130.0806			H7=H-90	1	H7=H-90	2	-	-				
AYPC.SL130.0807			L6=L <sub>EF</sub> -5	3	L6=L <sub>EF</sub> -5	3	L6=L <sub>EF</sub> -5	3				
AYPC.SL130.1901			L7=L1-27,5	1	L7=L1-27,5	2	L7=L1-27,5	2				
			H8=H1-55*	1	H8=H1-55*	2	H8=H1-55*	2				
AYPC.SL130.1903			H9=H1-10	2	H9=H1-10	4	H9=H1-10	4				
AYPC.SL130.1905			L8=L <sub>EF</sub> -56**	2	L8=L <sub>EF</sub> -56**	2	L8=L <sub>EF</sub> -56**	2				
AYPC.SL130.1950			L9=L <sub>EF</sub> -92	1	L9=L <sub>EF</sub> -90	1	L9=L <sub>EF</sub> -94	1				

Article	Drawing	1..					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0940HS-01							
		2	1	4	2	4	2
AYPC.SL130.0940S-01							
		-	1	-	2	-	2
AYPC.SL130.0941HS-01		1	-	2	-	2	-
AYPC.SL130.0981		4	4	4	4	4	4
AYPC.SL130.0985		-	2	-	4	-	4
AYPC.SL130.0950-02		8	8	16	16	16	16
AYPC.SL130.0951		8	8	8	8	16	16
AYPC.SL130.0905		5	5	2	2	10	10
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0907		1	1	2	2	2	2
AYPC.SL130.0908		3	3	3	3	3	3
AYPC.W62.0912		4	4	4	4	8	8
AYPC.W62.0913		4	4	8	8	8	8
AYPC.SL130.0918		8	8	8	8	12	12
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL130.0925		N***	N***	N***	N***	N***	N***
AYPC.SL130.0943		4	4	4	4	4	4
AYPC.SL130.0944		4	4	4	4	4	4
AYPC.SL130.0947		11	11	11	11	11	11
AYPC.SL160.0928		5	5	2	2	10	10

Article	Drawing	1..					
		Type A1 Type A2		Type A5 Type A6		Type A7 Type A8	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500	LEF/500	LEF/500
AYPC.W62.0901M		8	8	12	12	16	16
100x50x3		10	10	16	16	20	20
FRK170		8	8	12	12	16	16
FRK177		8	4	12	4	12	8
FRK178		4	2	6	2	6	4
FRK178-01		4	2	6	2	6	4

Article	Drawing	Type A1 Type A2				Type A5 Type A6				Type A7 Type A8			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..		1..		1..
Gaskets													
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	L1x2	1	L1x2	3	L1x2	1	L1x2	4	L1x2	2
FRK175		L1x2+H1x2	2	L1x2+H1x4	1	L1x3+H1x2	2	L1+H1x2	2	L1x4+H1x3	2	L1x2+H1x3	2
FRK188		2xL8	1	2xL8	1	2xL8	1	2xL8	1	L8	2	L8	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	3	(A+B)x2	3	(A+B)x2	4	(A+B)x2	4
FRK230		H9	2	H9	2	H9	4	H9	4	H9	4	H9	4
ISE01		L5+H6x2	1	L5+H6x2	1	L5+H6	2	L5+H6	2	L5+H6x2	1	L5+H6x2	1
IS10		H9	2	H9	2	H9	4	H9	4	H9	4	H9	4
AYPC.SL130.0912		-	-	L1x4	1	-	-	L1x4	2	-	-	L1x2	4

Infill			
Type A1 Type A2	Type A5 Type A6	Type A7 Type A8	
A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	3
A=L1-85; B=H1-154	4	A=L1-85; B=H1-154	4

Variant	AYPC.SL130.0925 quantity, N, pcs		
	Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
1	-	-	-
2	2	4	4
3	4	8	8
4	4	8	8

Article	Drawing	1..		
		Type A1 Type A2	Type A5 Type A6	Type A7 Type A8
Hardware				
3,9x25-A2ISO14585		26	20	36
4,8x45-A2ISO14585		5	2	10
3,9x19-A2ISO14586		H9/150	H9/75	H9/75
3,9x13-A2ISO14586		L6/100	L6/100	L6/100
5x10DIN6325D		16	16	28
5x14DIN6325D		-	-	4

1. When manufacturing types A5, A6 and A7, A8 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).


2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.

\*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.


\*\*\*AYPC.SL130.0925 cover is used only with sash profile AYPC.SL130.0203 or AYPC.SL130.0204 (see application table).





SL130 HS

SL130 S




Type C1


Type C3

Type C4

Vertical sections





























Horizontal sections



Infill					
Type C1		Type C3		Type C4	
A=L1-154; B=H1-154	1	A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	2
A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	2

The distance to transom insert axle, L <sub>0</sub>		
Type C1	Type C3	Type C4
$L_0 = L_{EF}/2 - 71,5$	$L_0 = L_{EF}/3 + 2,5$	$L_0 = L_{EF}/4 - 50$

Article	Drawing	Type C1		Type C3		Type C4		
			1...		1...		1...	
Profile								
AYPC.SL130.0103			L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2
AYPC.SL130.0105			H	2	H	2	H	2
AYPC.SL130.0201			L1=L <sub>EF</sub> /2+43,5	2	L1=L <sub>EF</sub> /3+30,5	4	L1=L <sub>EF</sub> /4+65	4
			H1=H-73	2	H1=H-73	4	H1=H-73	3
			H2=H-56	1	H2=H-56	2	H2=H-56	2
AYPC.SL130.0205			-	-	-	-	H3=H-73	1
AYPC.SL130.0601			L2=L1-138	4	L2=L1-138	6	L2=L1-138	8
			H4=H1-182	2	H4=H1-182	4	H4=H1-182	4
			H5=H-100	2	H5=H-100	2	H5=H-100	4
AYPC.SL130.0611			H6=H5	1	-	-	H6=H5	2
			L3=L2-22	2	L3=L2-44	2	L3=L2-22	4
AYPC.SL130.0801			H7=H1	1	H7=H1	2	H7=H1	2
			H8=H-56	1	H8=H-56	2	H8=H-56	2
AYPC.SL130.0803			L4=L <sub>EF</sub> /2-40	2	L4=L <sub>EF</sub> /3-53	4	L4=L <sub>EF</sub> /2-66	2
AYPC.SL130.0804			H9=H-92	1	H9=H-92	2	-	-
AYPC.SL130.0805-01			H10=H-59	1	-	-	H10=H-59	2
AYPC.SL130.0806			H11=H-90	1	H11=H-90	2	-	-
AYPC.SL130.0807			L5=L <sub>EF</sub> -5	2	L5=L <sub>EF</sub> -5	2	L5=L <sub>EF</sub> -5	2
AYPC.SL130.1901			L6=L1-57	1	L6=L1-57	2	L6=L1-57	2
			H12=H1-55*	1	H12=H1-55*	2	H12=H1-55*	2
AYPC.SL130.1902			H13=H1-10	1	H13=H1-10	2	H13=H1-10	2
			H14=H-72	1	H14=H-72	2	H14=H-72	2
AYPC.SL130.1904			L7=L <sub>EF</sub> -56**	2	L7=L <sub>EF</sub> -56**	2	L7=L <sub>EF</sub> -56**	2
AYPC.SL130.1906			L8=L <sub>EF</sub> /2-30,5	2	L8=L <sub>EF</sub> /3-43,5	4	L8=L4+18	2
			H15=H-72	1	H15=H-72	2	-	-
AYPC.SL160.1950			L9=L <sub>EF</sub> -94	1	L9=L <sub>EF</sub> -94	1	L9=L <sub>EF</sub> -94	1

Article	Drawing	1..					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0940HS		1	-	2	-	2	-
AYPC.SL130.0940S		-	1	-	2	-	2
AYPC.SL130.0942HS		1	-	2	-	2	-
AYPC.SL130.0986-01		-	2	-	4	-	4
AYPC.SL130.0950-02		4	4	8	8	8	8
AYPC.SL130.0951		8	8	16	16	16	16
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0908		2	2	2	2	2	2
AYPC.W62.0912		4	4	8	8	8	8
AYPC.SL130.0918		8	8	16	16	12	12
AYPC.SL130.0933K		-	-	-	-	2	2
AYPC.SL130.0943		2	2	2	2	2	2
AYPC.SL130.0944		2	2	2	2	2	2
AYPC.SL130.0945		8	8	8	8	8	8
AYPC.SL130.0947		9	9	9	9	9	9
AYPC.SL130.0982		2	2	2	2	2	2
AYPC.SL160.0928		H13/150	H13/150	H13/75	H13/75	H13/75	H13/75
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500	LEF/500	LEF/500
100x22x5		4	4	4	4	8	8
100x32x2		3	3	2	2	6	6
AYPC.W62.0901M		5	5	10	10	10	10
100x50x3		13	13	18	18	26	26
FRK170		8	8	12	12	16	16

Article	Drawing	1..					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
FRK177		4	-	8	-	4	-
FRK178		2	-	4	-	2	-
FRK178-01		2	-	4	-	2	-

Article	Drawing	Type C1				Type C3				Type C4			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..		1..		1..
Gaskets													
FRK29-01		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK176		L1x2	1	-	-	L1x2	2	-	-	L1x2	2	-	-
FRK175		L1x2+H1x2	1	H1x2	1	L1x2+H1x2	2	H1x2	2	L1x2+H1	2	H1x2	1
FRK188		L9	1	L9	1	L9	1	L9	1	L9	1	L9	1
FRK191		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK230		H1	2	H1	2	H1	4	H1	4	H1	4	H1	4
ISE01		2xH14+H10+H9+2xL4	1	2xH14+H10+H9+2xL4	1	2xH14+H9+2xL4	2	2xH14+H9+2xL4	2	2xH14+H10+L4	2	2xH14+H10+L4	2
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x4	2

Article	Drawing	1..		
		Type C1	Type C3	Type C4
Hardware				
3,9x9,5-A2IS014585		H13/150	H13/75	H13/75
3,9x25-A2IS014585		16	16	16
3,9x13-A2IS014586		LEF/150	LEF/150	LEF/150
3,9x19-A2IS014586		L8/250+H15/500+L3/250+H6/500	L8/125+L3/250+H15/250	L8/250+L3/250+H6/250
5x10DIN6325D		16	32	28
5x14DIN6325D		-	-	4




1. When manufacturing types C3 and C4 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).


2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.


\*\*The length of AYPC.SL130.1904 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 HS




SL130 S




Type C1




Type C3




Type C4




Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2























Horizontal sections. Variant 3




Horizontal sections. Variant 4



Article	Drawing		Type C1		Type C3		Type C4	
				1...		1...		1...
Profile								
AYPC.SL130.0103			L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2
AYPC.SL130.0105			H	2	H	2	H	2
AYPC.SL130.0201			L1=L <sub>EF</sub> /2-0,5	1	L1=L <sub>EF</sub> /3-5	2	L1=L <sub>EF</sub> /4+21	2
			L1=L <sub>EF</sub> /2-0,5	1	L1=L <sub>EF</sub> /3-5	2	L1=L <sub>EF</sub> /4+21	2
			H1=H-73	1	H1=H-73	2	H1=H-73	1
Select	Variant 1							
	AYPC.SL130.0202		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2
			H3=H-56	1	H3=H-56	2	H3=H-56	2
	Variant 2							
	AYPC.SL130.0202		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2
	AYPC.SL130.0204		H3=H-56	1	H3=H-56	2	H3=H-56	2
	Variant 3							
	AYPC.SL130.0203		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2
	AYPC.SL130.0202		H3=H-56	1	H3=H-56	2	H3=H-56	2
	Variant 4							
AYPC.SL130.0203		H2=H1-55	1	H2=H1-55	2	H2=H1-55	2	
AYPC.SL130.0204		H3=H-56	1	H3=H-56	2	H3=H-56	2	
AYPC.SL130.0205			-	-	-	-	H4=H-73	1
AYPC.SL130.0601			L2=L1-69	4	L2=L1-69	6	L2=L1-69	8
			H5=H1-182	2	H5=H1-182	4	H5=H1-182	4
			H6=H-100	2	H6=H-100	2	H6=H-100	4
AYPC.SL130.0611			H7=H-100	1	-	-	H7=H-100	2
			L3=L2-22	2	L3=L2-44	2	L3=L2-22	4
AYPC.SL130.0802			H8=H1	1	H8=H1	2	H8=H1	2
			H9=H-56	1	H9=H-56	2	H9=H-56	2
AYPC.SL130.0803			L4=L <sub>EF</sub> /2-14,5	2	L4=L <sub>EF</sub> /3-19	4	L4=2*L1-58	2
AYPC.SL130.0804			H10=H-92	1	H10=H-92	2	-	-
AYPC.SL130.0805-01			H11=H-59	1	-	-	H11=H-59	2
AYPC.SL130.0806			H12=H-90	1	H12=H-90	2	-	-

Article	Drawing		Type C1		Type C3		Type C4	
				1...		1...		1...
Profile								
AYPC.SL130.0807			L5=L <sub>EF</sub> -5	2	L5=L <sub>EF</sub> -5	2	L5=L <sub>EF</sub> -5	2
AYPC.SL130.1901			L6=L1-27,5	1	L6=L1-27,5	2	L6=L1-27,5	2
			H13=H1-55*	1	H13=H1-55*	2	H13=H1-55*	2
AYPC.SL130.1903			H14=H1-10	1	H14=H1-10	2	H14=H1-10	2
			H15=H-72	1	H15=H-72	2	H15=H-72	2
AYPC.SL130.1904			L7=L <sub>EF</sub> -56**	2	L7=L <sub>EF</sub> -56**	2	L7=L <sub>EF</sub> -56**	2
AYPC.SL130.1906			L8=L <sub>EF</sub> /2-10,5	2	L8=L <sub>EF</sub> /3-15	4	L8=L <sub>EF</sub> /2-8	2
			H16=H-72	1	H16=H-72	2	-	-
AYPC.SL160.1950			L9=L <sub>EF</sub> -94	1	L9=L <sub>EF</sub> -94	1	L9=L <sub>EF</sub> -94	1

Article	Drawing	1..					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0940HS-01		1	-	2	-	2	-
							
							
AYPC.SL130.0940S-01		-	1	-	2	-	2
							
							
AYPC.SL130.0942HS-01		1	-	2	-	2	-
AYPC.SL130.0985-01		-	2	-	4	-	4
AYPC.SL130.0950		4	4	8	8	8	8
AYPC.SL130.0950-02		4	4	8	8	8	8
AYPC.SL130.0951		4	4	8	8	8	8
AYPC.SL130.0906		4	4	8	8	8	8
AYPC.SL130.0908		2	2	2	2	2	2
AYPC.W62.0912		2	2	4	4	4	4
AYPC.W62.0913		2	2	4	4	4	4
AYPC.SL130.0918		4	4	8	8	4	4
AYPC.SL130.0925		N***	N***	N***	N***	N***	N***
AYPC.SL130.0933K		-	-	-	-	2	2

Article	Drawing	1...					
		Type C1		Type C3		Type C4	
		SL130 HS	SL130 S	SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories							
AYPC.SL130.0943		2	2	2	2	2	2
AYPC.SL130.0944		2	2	2	2	2	2
AYPC.SL130.0945		8	8	8	8	8	8
AYPC.SL130.0947		10	10	10	10	10	10
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500	LEF/500	LEF/500
AYPC.SL130.0982		2	2	2	2	2	2
100x22x5		4	4	4	4	8	8
100x32x2		3	3	2	2	6	6
AYPC.W62.0901M		5	5	10	10	10	10
100x50x3		13	13	18	18	26	26
FRK170		8	8	12	12	16	16
FRK177		4	-	8	-	4	-
FRK178		2	-	4	-	2	-
FRK178-01		2	-	4	-	2	-

Article	Name Drawing	Type C1				Type C3				Type C4			
		SL130 HS		SL130 S		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1...		1...		1...		1...		1...		1...
Gaskets													
FRK29-01		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK176		L1x2	1	-	-	L1x2	2	-	-	L1x2	2	-	-
FRK175		L1x2+H1x2	1	H1x2	1	L1x2+H1x2	2	H1x2	2	L1x2+H1	2	H1x2	1
FRK188		L9	1	L9	1	L9	1	L9	1	L9	1	L9	1
FRK191		(A+B)+(A+B1)	2	(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	2x(A+B)+(A+B1)	2	(A+B)+(A+B1)	4	(A+B)+(A+B1)	4
FRK230		H1	2	H1	2	H1	4	H1	4	H1	4	H1	4
ISE01		2xL4+H10+H11	1	2xL4+H10+H11	1	2xL4+H10	2	2xL4+H10	2	L4+H11	2	L4+H11	2
IS10		H14	2	H14	2	H14	4	H14	4	H14	4	H14	4
AYPC.SL130.0912		-	-	L1x2	2	-	-	L1x2	4	-	-	L1x2	4

Article	Drawing	1..		
		Type C1	Type C3	Type C4
Hardware				
3,9x25-A2 ISO14585		16	16	16
3,9x13-A2 ISO14586		LHP/150	LHP/150	LHP/150
3,9x19-A2 ISO14586		L8/250+L3/250+H7/500+ +H14/150+H16/500	L8/125+L3/250+H14/75+ +H16/250	L8/250+L3/125+H7/250+ +H14/75
5x10 DIN6325D		8	16	12
5x14 DIN6325		-	-	4

Infill					
Type C1		Type C3		Type C4	
A=L1-85; B=H1-154	1	A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	2
A=L1-85; B1=H-72	1	A=L1-85; B1=H-72	1	A=L1-85; B1=H-72	2

The distance to transom insert axle, L <sub>0</sub>		
Type C1	Type C3	Type C4
$L_0 = L_{EF}/2 - 57,5$	$L_0 = L_{EF}/3 - 3$	$L_0 = L_{EF}/4 - 36$

Variant	AYPC.SL130.0925 quantity, N, pcs		
	Type C1	Type C3	Type C4
1	-	-	-
2	2	4	4
3	4	8	8
4	4	8	8

1. When manufacturing types C3 and C4 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).



2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.


\*\*The length of AYPC.SL130.1904 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.

\*\*\*AYPC.SL130.0925 cover is used only with sash profile AYPC.SL130.0203 or AYPC.SL130.0204 (see application table).













Vertical sections



Horizontal sections



Article	Drawing		Type A3		Type A9 Type A10	
				1...		1...
Profile						
AYPC.SL130.0101			L=LEF-56	2	L=LEF-56	2
AYPC.SL130.0106			H	2	H	2
AYPC.SL130.0201			L1=LEF/2+5	4	L1=LEF/4+26,5	8
			H1=H-73	4	H1=H-73	7
AYPC.SL130.0205			-	-	H2=H1	1
AYPC.SL130.0601			L2=L1-138	4	L2=L1-138	8
			H3=H1-182	4	H3=H1-182	8
AYPC.SL130.0801			H4=H1	2	H4=H1	4
AYPC.SL130.0805-01			H5=H-59	2	H5=H-59	2
AYPC.SL130.0806			H6=H-90	2	H6=H-90	2
AYPC.SL130.0807			L3=LEF-5	3	L3=LEF-5	3
AYPC.SL130.1901			L4=L1-57	2	L4=L1-57	4
			H7=H1-55*	2	H7=H1-55*	4
AYPC.SL130.1902			H8=H1-10	2	H8=H1-10	4
AYPC.SL130.1905			L5=LEF-56**	2	L5=LEF-56**	2
AYPC.SL160.1950			L6=LEF-94	2	L6=LEF-94	2

Article	Drawing	1...			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0940HS		2	-	4	-
AYPC.SL130.0940S		-	2	-	4
AYPC.SL130.0941HS		1	-	2	-
AYPC.SL130.0981		4	4	4	4
AYPC.SL130.0986		-	2	-	4
AYPC.SL130.0951		16	16	32	32
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0907		1	1	2	2
AYPC.SL130.0908		3	3	3	3
AYPC.W62.0912		8	8	16	16
AYPC.SL130.0918		16	16	28	28
AYPC.SL130.0933K		-	-	2	2
AYPC.SL160.0928		H8/150	H8/150	H8/75	H8/75
AYPC.SL130.0943		4	4	4	4
AYPC.SL130.0944		4	4	4	4
AYPC.SL130.0947		11	11	11	11
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500
AYPC.W62.0901M		8	8	16	16
100x50x3		12	12	24	24
FRK170		8	8	16	16
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-

Article	Drawing	Type A3				Type A9 Type A10			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..
Gaskets									
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	-	-	L1x2	4	-	-
FRK175		L1x2+H1x2	2	H1x2	2	L1x4+H1x3	2	H1x3	2
FRK188		L6x2	1	L6x2	1	L6x2	1	L6x2	1
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK230		H8	2	H8	2	H8	4	H8	4
ISE01		2xH8+2xH5	1	2xH8+2xH5	1	2xH5+4xH8	1	2xH5+4xH8	1
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8

Article	Drawing	1..	
		Type A3	Type A9 Type A10
Hardware			
3,9x9,5-A2ISO14585		H8/150	H8/75
3,9x25-A2ISO14585		16	16
3,9x13-A2ISO14586		L3/100	L3/100
5x10DIN6325D		32	60
5x14DIN6325D		-	4

Infill			
Type A3		Type A9 Type A10	
A=L1-154, B=H1-154	2	A=L1-154, B=H1-154	4




1. When manufacturing types A9 and A10 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).


2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.


\*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 HS




SL130 S





Type A3





Type A9




Type A10




Vertical sections




Horizontal sections. Variant 1




Horizontal sections. Variant 2

















Horizontal sections. Variant 3







Horizontal sections. Variant 4



Article	Drawing		Type A3		Type A9 Type A10	
				1...		1...
Profile						
AYPC.SL130.0101			L=LEF-56	2	L=LEF-56	2
AYPC.SL130.0106			H	2	H	2
AYPC.SL130.0201			L1=LEF/2-39	2	L1=LEF/4-17,5	4
			L2=L1	2	L2=L1	4
			H1=H-73	2	H1=H-73	3
Select	Variant 1					
	AYPC.SL130.0202				2	4
	Variant 2					
	AYPC.SL130.0202				1	2
	AYPC.SL130.0204				1	2
	Variant 3					
	AYPC.SL130.0202				1	2
	AYPC.SL130.0203				1	2
	Variant 4					
AYPC.SL130.0203			1	2		
AYPC.SL130.0204			1	2		
AYPC.SL130.0205			-	-	H3=H1	1
AYPC.SL130.0601			L3=L1-69	4	L3=L1-69	8
			H4=H1-182	4	H4=H1-182	8
AYPC.SL130.0802			H5=H1	2	H5=H1	4
AYPC.SL130.0805-01			H6=H-59	2	H6=H-59	2
AYPC.SL130.0806			H7=H-90	2	H7=H-90	2
AYPC.SL130.0807			L4=LEF-5	3	L4=LEF-5	3
AYPC.SL130.1901			L5=L1-27,5	2	L5=L1-27,5	4
			H8=H1-55*	2	H8=H1-55*	4
AYPC.SL130.1903			H9=H1-10	2	H9=H1-10	4
AYPC.SL130.1905			L6=LEF-56**	2	L6=LEF-56**	2
AYPC.SL160.1950			L7=LEF-94	2	L7=LEF-94	2

Article	Drawing	1...			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0940HS-01		2	-	4	-
AYPC.SL130.0940S-01		-	2	-	4
AYPC.SL130.0941HS-01		1	-	2	-
AYPC.SL130.0981		4	4	4	4
AYPC.SL130.0985		-	2	-	4
AYPC.SL130.0950-02		8	8	16	16
AYPC.SL130.0951		8	8	16	16
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0907		1	1	2	2
AYPC.SL130.0908		3	3	3	3
AYPC.W62.0912		4	4	8	8
AYPC.W62.0913		4	4	8	8
AYPC.SL130.0918		8	8	12	12
AYPC.SL130.0925		N***	N***	N***	N***
AYPC.SL130.0933K		-	-	2	2
AYPC.SL130.0943		4	4	4	4
AYPC.SL130.0944		4	4	4	4
AYPC.SL130.0947		12	12	12	12
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500
AYPC.W62.0901M		8	8	16	16
100x50x3		12	12	24	24
FRK170		8	8	16	16

Article	Drawing	1..			
		Type A3		Type A9 Type A10	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-

Article	Drawing	Type A3				Type A9 Type A10			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1..		1..		1..		1..
Gaskets									
FRK29-01		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK176		L1x2	2	-	-	L1x2	4	-	-
FRK175		L1x2+H1x4	2	H1x2	2	L1x4+H1x3	2	H1x3	2
FRK188		2xL7	1	2xL7	1	L7	2	L7	2
FRK191		(A+B)x2	2	(A+B)x2	2	(A+B)x2	4	(A+B)x2	4
FRK230		H9	2	H9	2	H9	4	H9	4
ISE01		H5	2	H5	2	H5	2	H5	2
IS10		H9	2	H9	2	H9	4	H9	4
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8



Article	Drawing	1..	
		Type A3	Type A9 Type A10
Hardware			
3,9x25-A2ISO14585		16	16
3,9x13-A2ISO14586		L4/100	L4/100
3,9x19-A2ISO14586		H9/150	H9/75
5x10DIN6325D		16	28
5x14DIN6325D		-	4

Infill			
Type A3		Type A9 Type A10	
A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	4


Variant	AYPC.SL130.0925 quantity, N, pcs	
	Type A3	Type A9 Type A10
1	-	-
2	2	4
3	2	4
4	4	8




1. When manufacturing types A9 and A10 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.31).
  2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).
- \*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.  
 \*\*The length of AYPC.SL130.1905 profile is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.












Vertical sections












Vertical sections




Article	Drawing	 Profile	Type D1		Type D5	
				1...		1...
AYPC.SL130.0107			L=L <sub>EF</sub> -56	2	L=L <sub>EF</sub> -56	2
AYPC.SL130.0109			H	2	H	2
AYPC.SL130.0201			L1=L <sub>EF</sub> /3+56,5	4	L1=L <sub>EF</sub> /6+70,5	8
			H1=H-73	4	H3=H-73	7
			H2=H-56	1	H2=H-56	2
AYPC.SL130.0205			-	-	H3=H-73	1
AYPC.SL130.0601			L2=L1-138	6	L2=L1-138	12
			H4=H1-182	4	H4=H1-182	8
			H5=H1-100	2	H5=H1-100	4








Vertical sections




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.0611			H6=H5	1	H6=H5	2
			L3=L2-22	2	L3=L2-22	4
AYPC.SL130.0801			H7=H1	3	H7=H1	6
			H8=H-56	1	H8=H-56	2
AYPC.SL130.0803			L4=2xLEF/3-52,5	2	L4=2xLEF/3-77,5	2
			H9=H-92	1	-	-
AYPC.SL130.0805-01			H10=H-59	3	H10=H-59	4
AYPC.SL130.0806			H11=H-90	1	-	-
AYPC.SL130.0807			L5=LEF-5	2	L5=LEF-5	2

Horizontal sections



Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.1901 for SL130 HS lift and slide option			L6=L1-57	2	L6=L1-57	4
			H12=H1-55**	2	H12=H1-55**	4
AYPC.SL130.1901 for SL130 S sliding option			L6=L1-57	1	L6=L1-57	1
			L6=L1-57	1	L6=L1-57	3
			H12=H1-55**	1	H12=H1-55**	1
AYPC.SL130.1902			H13=H1-10	3	H13=H1-10	6
			H14=H-72	1	H14=H-72	2
AYPC.SL130.1904			L7=LEF-56**	2	L7=LEF-56**	2
AYPC.SL130.1905			L8=LEF-56**	2	L8=LEF-56**	2
AYPC.SL130.1906			L9=2xLEF/3-43,5	2	L9=2xLEF/3-59,5	2
			H15=H-56	1	-	-
AYPC.SL130.1950			L10=LEF-94	2	L10=LEF-94	2

Horizontal sections



Article	Drawing	Type D1				Type D5			
		SL130 HS		SL130 S		SL130 HS		SL130 S	
			1...		1...		1...		1...
Gaskets									
FRK29-01		(A+B)x2	3	(A+B)x2	3	(A+B)x2	6	(A+B)x2	6
FRK176		L1x2	2	-	-	L1x2	4	-	-
FRK175		L1x2+H1	2	H1x2	1	L1x4+H1	2	H1x2	1
FRK188		L10	2	L10	2	L10	2	L10	2
FRK191		(A+B)x2	3	(A+B)x2	3	(A+B)x2	6	(A+B)x2	6
FRK230		H13	4	H13	4	H13	8	H13	8
ISE01		L4+H10x2+H13x2	2	L4+H10x2+H13x2	2	L4+H10x2+H13x4	2	L4+H10x2+H13x4	2
AYPC.SL130.0912		-	-	L1x2	4	-	-	L1x2	8

Article	Drawing	1..			
		Type D1		Type D5	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
AYPC.SL130.0940HS		3	-	6	-
AYPC.SL130.0940S		-	3	-	6
AYPC.SL130.0941HS		1	-	2	-
AYPC.SL130.0942HS		1	-	2	-
AYPC.SL130.0943		4	4	4	4
AYPC.SL130.0944		2	2	2	2
AYPC.SL130.0945		4	4	4	4
AYPC.SL130.0946		4	4	4	4
AYPC.SL130.0947		13	13	13	13
AYPC.SL130.0983		2	2	2	2
AYPC.SL130.0986		-	2	-	4
AYPC.SL130.0986-01		-	2	-	4
AYPC.SL130.0950-02		4	4	8	8
AYPC.SL130.0951		16	16	32	32
AYPC.SL130.0906		8	8	16	16
AYPC.SL130.0908		2	2	2	2
AYPC.SL130.0912		8	8	16	16
AYPC.SL130.0918		16	16	28	28
AYPC.SL130.0933K		-	-	2	2
AYPC.SL160.0928		H14/75	H14/75	H14/37,5	H14/37,5
AYPC.100P.1850		LEF/500	LEF/500	LEF/500	LEF/500
100x22x5		4	4	8	8

Article	Drawing	1...			
		Type D1		Type D5	
		SL130 HS	SL130 S	SL130 HS	SL130 S
Accessories					
100x32x2		3	3	6	6
AYPC.W62.0901M		9	9	18	18
100x50x3		19	19	38	38
FRK170		12	12	24	24
FRK177		8	-	12	-
FRK178		4	-	6	-
FRK178-01		4	-	6	-


Article	Drawing	1...	
		Type D1	Type D5
Hardware			
3,9x9,5-A2ISO14585		H14/75	H14/37,5
3,9x25-A2ISO14585		24	24
3,9x13-A2ISO14586		L5/150	L5/150
3,9x19-A2ISO14586		L3/250+L9/250+H6/500+H15/500	L3/125+L9/250+H6/250
5x10DIN6325D		32	60
5x14DIN6325D		-	4

Infill			
Type D1		Type D5	
A=L1-154; B=H1-154	2	A=L1-154; B=H1-154	4
A=L1-154; B1=H-72	1	A=L1-154; B1=H-72	2


The distance to transom insert axle, L <sub>0</sub>	
Type D1	Type D5
$L_0 = L_{EF}/3-58,5$	$L_0 = L_{EF}/6-44$




- When manufacturing types C3 and C4 doors with the width L>6500 mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).
- Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 - Table of Glazing).
- \* The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 - 08.44 for profile dimensions and cutting.
- \*\* The length of AYPC.SL130.1904 and AYPC.SL130.1905 profiles is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.




SL130 S




Type D1




Type D5









Vertical sections











Vertical sections




Article	Drawing	 Profile	Type D1		Type D5		
			 L	1...	 L	1...	
AYPC.SL130.0107			L=LEF-56	2	L=LEF-56	2	
AYPC.SL130.0109			H	2	H	2	
AYPC.SL130.0201			L1=LEF/3+20,5	1	L1=LEF/6+35	2	
			L1=LEF/3+20,5	1	L1=LEF/6+35	2	
			H1=H-73	1	H1=H-73	1	
			L2=LEF/3-48,5	2	L2=LEF/6-34	4	
Select	Variant 1						
	AYPC.SL130.0202			H2=H1-55	3	H2=H1-55	6
				H3=H-56	1	H3=H-56	2
	Variant 2						
	AYPC.SL130.0202			H2=H1-55	2	H2=H1-55	4
	AYPC.SL130.0204			H2=H1-55	1	H2=H1-55	2
			H3=H-56	1	H3=H-56	2	






Vertical sections




Article	Drawing		Type D1		Type D5		
				1...		1...	
	Variant 3						
AYPC.SL130.0203			H2=H1-55	2	H2=H1-55	4	
AYPC.SL130.0202			H2=H1-55	1	H2=H1-55	2	
			H3=H-56	1	H3=H-56	2	
	Variant 4						
AYPC.SL130.0203			H2=H1-55	2	H2=H1-55	4	
AYPC.SL130.0204			H2=H1-55	1	H2=H1-55	2	
		H3=H-56	1	H3=H-56	2		
AYPC.SL130.0205			-	-	H4=H-73	1	



Horizontal sections. Variant 1




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.0601			L3=L1-69	4	L3=L1-69	8
			L4=L2	2	L4=L2	4
			H5=H1-182	4	H5=H1-182	8
			H6=H-100	2	H6=H-100	4
AYPC.SL130.0611			H7=H-100	1	H7=H-100	2
			L5=L3-22	2	L5=L3-22	4
AYPC.SL130.0802			H8=H-73	3	H8=H-73	6
			H9=H-56	1	H9=H-56	2
AYPC.SL130.0803			L6=2xLEF/3-35,5	2	L6=2xLEF/3-44	2
			H9=H-92	1	-	-
AYPC.SL130.0805-01			H10=H-59	3	H10=H-59	4
AYPC.SL130.0807			L7=LEF-5	2	L7=LEF-5	2

Horizontal sections. Variant 2




Article	Drawing		Type D1		Type D5	
				1...		1...
AYPC.SL130.1901			L8=L1-27,5	1	L8=L1-27,5	2
			L9=L2	1	L9=L2	2
			H11=H1-55*	1	H11=H1-55*	2
AYPC.SL130.1903			H12=H1-10	3	H12=H1-10	6
			H13=H-72	1	H13=H-72	2
AYPC.SL130.1904			L10=L <sub>EF</sub> -56**	2	L10=L <sub>EF</sub> -56**	2
AYPC.SL130.1905			L11=L <sub>EF</sub> -56**	2	L11=L <sub>EF</sub> -56**	2
AYPC.SL130.1906			L12=2xL <sub>EF</sub> /3-22	2	L12=2xL <sub>EF</sub> /3-36	2
			H15=H-56	1	-	-
AYPC.SL130.1950			L13=L <sub>EF</sub> -94	2	L13=L <sub>EF</sub> -94	2

Horizontal sections. Variant 3





Article	Drawing	1..	
		Type D1	Type D5
	Accessories		
AYPC.SL130.0940S-01		3	6
AYPC.SL130.0943		4	4
AYPC.SL130.0944		2	2
AYPC.SL130.0945		4	4
AYPC.SL130.0946		4	4
AYPC.SL130.0947		14	14

Horizontal sections. Variant 4



Article	Drawing	1..	
		Type D1	Type D5
Accessories			
AYPC.SL130.0983		2	2
AYPC.SL130.0985		2	4
AYPC.SL130.0985-01		2	4
AYPC.SL130.0950		4	8
AYPC.SL130.0950-02		12	24
AYPC.SL130.0951		4	8
AYPC.SL130.0906		8	16
AYPC.SL130.0908		2	2
AYPC.SL130.0912		2	4

Article	Drawing	1..	
		Type D1	Type D5
Accessories			
AYPC.SL130.0918		4	4
AYPC.W62.0913		6	12
AYPC.SL130.0925		N***	N***
AYPC.SL130.0933K		-	2
AYPC.100P.1850		LEF/500	LEF/500
100x22x5		4	8
100x32x2		3	6
AYPC.W62.0901M		9	18
100x50x3		19	38
FRK170		12	24

Article	Drawing	Type D1		Type D5	
			1..		1..
Gaskets					
FRK29-01		(A+B)x2	3	(A+B)x2	6
FRK175		H1x2	1	H1x2	1
FRK188		L13	2	L13	2
FRK191		(A+B)x2	3	(A+B)x2	6
FRK230		H13	4	H13	8
ISE01		L6x2+H9+H10x3	1	L6+H10x2	2
IS10		H13	4	H13	8
AYPC.SL130.0912		L1x2	4	L1x2	8

Article	Drawing	1..	
		Type D1	Type D5
Hardware			
3,9x25-A2ISO14585		24	24
3,9x13-A2ISO14586		L7/150	L7/150
3,9x19-A2ISO14586		L5/250+L12/250+H7/500+H13/75+H15/500	L5/125+L12/250+H7/250+H13/37,5
5x10DIN6325D		8	12
5x14DIN6325D		-	4

Infill			
Type D1		Type D5	
A=L1-85; B=H1-154	2	A=L1-85; B=H1-154	4
A=L1-85; B1=H-72	1	A=L1-85; B1=H-72	2

The distance to transom insert axle, $L_0$	
Type D1	Type D5
$L_0 = L_{EF}/3-36$	$L_0 = L_{EF}/6-22$

Variant	AYPC.SL130.0925 quantity, N, pcs	
	Type D1	Type D5
1	-	-
2	4	8
3	4	8
4	8	16

1. When manufacturing types C3 and C4 doors with the width  $L > 6500$  mm, it is necessary to install additional frame connectors and encapsulating inserts (see page 08.32).

2. Select glass bead profiles and rubber gaskets according to the infill thickness (see section 05 – Table of Glazing).

\*The length of AYPC.SL130.1901 profile is given for calculation of the required quantity. See pages 08.43 – 08.44 for profile dimensions and cutting.

\*\*The length of AYPC.SL130.1904 and AYPC.SL130.1905 profiles is given for calculation of the required quantity. See page 08.34 for profile dimensions and cutting.

\*\*\*AYPC.SL130.0925 cover is used only with AYPC.SL130.0203 or AYPC.SL130.0204 sash profile (see application table).






**ALUTECH SL130**  
Patio systems

# PROFILE MACHINING AND ASSEMBLY




Table of symbols




LEF – external frame width;  
LIF – internal frame width;  
LCF – clear frame width;  
HEF – external frame height;  
HIF – internal frame height;  
HCF – clear frame height;

LES – external sash width;  
LIS – internal sash width;  
LCS – clear sash width;  
HES – external sash height;  
HIS – internal sash height;  
HCS – clear sash height;


HH – distance from sash bottom to handle axle;  
LG – glass width;  
LI – distance from vertical frame edge to ledge axle;  
LO – distance from horizontal frame edge to transom insert axle;  
HG – glass height.




Transom connection with sash profiles



Transom fixing elements  
Original profile – AYPCLSL130.0701





Transom connection with frame profiles



AYPCLSL130.0301 machining – Variant 2.

Cutting scheme for encapsulating inserts from AYPCLSL130.094.7



AYPCLSL130.0301 machining – Variant 3.


Profile 1	Profile 2	Transom fixing element		Lo, mm
		Article	Qty., pcs	
AYPCLSL130.0201	AYPCLSL130.0103 AYPCLSL130.0104 AYPCLSL130.0107 AYPCLSL130.0108	AYPCLSL130.0950-02	2	LL - 5
AYPCLSL130.0202		AYPCLSL130.0950	2	
AYPCLSL130.0203		AYPCLSL130.0950	2	LL + 9
AYPCLSL130.0204		AYPCLSL130.0950	2	
AYPCLSL130.0301	AYPCLSL130.0950-01	AYPCLSL130.0950-01	2	-

Do not mix up ledge axle LL with transom insert axle Lo!




Make the number of holes and the number of pins to be installed according to the instructions!  
Reducing the number of pins and holes will result in a loss of structural rigidity.  
Changing pins with self-tapping screws is not allowed!


Corner connection of AYPC.SL130.0108 frame profiles




Corner connection of AYPC.SL130.0107 and AYPC.SL130.0109 frame profiles




Corner connection of AYPC.SL130.0201 and AYPC.SL130.0205 sash profiles




Corner connection of AYPC.SL130.0104 frame profiles




Corner connection of AYPC.SL130.0103 and AYPC.SL130.0105 frame profiles




Corner connection of AYPC.SL130.0201 sash profiles




Corner connection of AYPC.SL130.0102 frame profiles








Corner connection of AYPC.SL130.0101 and AYPC.SL130.0106 frame profiles






Corner connection of AYPC.SL130.0201 and AYPC.SL130.0202 (0203, 0204) sash profiles









Frame profile machining for corner connection by pinning



The stop is shown schematically and depends on the equipment used




Profile machining for corner connection at  $\alpha = 90^\circ$  using self-tapping screws





Frame profile machining for longitudinal connection at  $L_{EF} > 6500$  mm


Frame profile machining for corner connection by pinning




Frame profile machining for corner connection by clamping



Profile machining for corner connection at  $\alpha = 90^\circ$



Profile machining for transom connection



The stop is shown schematically and depends on the equipment used

Frame corner connection assembly at  $\alpha = 45^\circ$

1

2

3

4

From outside!

Encapsulating insert

AYPC.SI.130.0907

COSMO HD-100.412

08.20

08.19

08.04

5

6

7

71

72

COSMO HD-100.412

Use a stop!

08.03

08.04

7

8

9

COSMO HD-100.412




COSMO CL-300.150

24h

Place the assembled product in the designated area until the adhesive dries completely, according to the recommendations of the adhesive producer.

Checked parameters of the assembled product	
Parameter	Max tolerance, mm
Nominal dimension range, mm	1.0
Difference in diagonal lengths	2.0
	3.0




Frame corner connection assembly at  $\alpha = 90^\circ$



Checked parameters of the assembled product	
Parameter	Max tolerance, mm
Nominal dimension range, mm	≤1000 1000-2000 >2000
Difference in diagonal lengths	10 2.0 3.0




Sash corner connection assembly at  $\alpha = 90^\circ$




Checked parameters of the assembled product	
Parameter	Max tolerance, mm
Nominal dimension range, mm	
Difference in diagonal lengths	
≤1000	1.0
1000-2000	2.0
>2000	3.0

T-shaped (transom) profile connection at  $\alpha = 90^\circ$




X-shaped (transom) profile connection at  $\alpha = 90^\circ$











Machining of drain holes in AYPC.SI.130.0103 and AYPC.SI.130.0104 frame profiles.




Outside view

















Machining of drain holes in AYPCL130.1904 and AYPCL130.1905 cover profiles.







Selection of encapsulation inserts



Assortment of encapsulating inserts



AYPC.SI.130.0947










Cutting scheme for encapsulating inserts from AYPC.SI.130.0947

Cutting scheme for encapsulating inserts from AYPC.SI.130.0946


Subsequent for sealing of bottom frame profile

1 Preparation of encapsulating inserts.



**Infill installation into the frame**

1 Installation of leveling and spacer supports




- 1 - leveling support set - see page 05.02,
- 2 - spacer support 100x12x5,
- 3 - auxiliary spacer support 100x12x22,
- 4 - AYPCL130.0982/L-01


AYPCL130.0982/L-01  
AYPCL130.0983/L-01

AYPCL130.0103  
AYPCL130.0107  
AYPCL130.0105  
AYPCL130.0109

Support installation under the infill




2 Installation of glass unit into intermediate position.  
AYPC.SL130.0611 edge profile installation.




Do not leave the glass unit unfixed

3 Installation of FRK29-01 gasket. For installation variants see page 08.24-25.  
Glass unit installation into permanent position.



Do not stretch the gasket!

4 Glass bead installation. Gasket installation under the glass bead.  
See page 05.02 for selection of glass bead and gasket size.




Manufacturer	Structural Sealant	Primer	Cleaner
Dow Corning	DC 993 DC 895	1200 OS Primer Primer C OS	R40 Cleaner P Cleaner 205
Sika	Sicasil SG-20 Sicasil SG-500	Aktivator-100	-
General Electric	SSG4400 SSG4000E	-	-
KÖMMERLING	Köttglaze S	-	-
Tremco	SG 490 SG 499	-	-


**Infill installation into the sash**

1 FRK29-01 gasket installation.  
For installation variants see page 08.24-25.

11





12




2 Bearing support installation.  
Support installation under the infill.

11





1 - AYPL W62.0901M bearing support;  
2 - leveling support.

3 Infill installation.  
Leveling support installation.




Support installation under the infill.

11



1 - AYPL W62.0901M bearing support;  
2 - leveling support.



4 Gasket bead installation. Gasket installation under the glass bead.  
See page 05.02 for selection of glass bead and gasket size.



Use AYPC.SI.130.0906 as bearing supports.



Leveling support





Manufacturer	Structural Sealant	Primer	Cleaner
Dow Corning	DC 993 DC 895	1200 OS Primer Primer C OS	R40 Cleaner P Cleaner 205
Sika	Sicasil SG-20 Sicasil SG-500	Aktivator-100	-
General Electric	SSG4400 SSG4000E	-	-
KÖMMERLING	Köttiglaze S	-	-
Trenco	SG 490 SG 499	-	-

AYPC.SI.130.0202  
AYPC.SI.130.0203  
AYPC.SI.130.0204







Machining and installation of FRK175, FRK176, FRK177, FRK178, FRK178-01 rubber corners and FRK177, FRK178, FRK178-01 EPDM corners




AYPC.SI.160.0904 and AYPC.SI.130.0909 leveler installation  
Installation scheme of AYPC.SI.160.0904 and AYPC.SI.130.0909 is the same



Machining of FRK177, FRK178, FRK178-01 corners during installation on AYPC.SI.130.0202, AYPC.SI.130.0203, AYPC.SI.130.0204 sashes




Cut FRK175, FRK176 gaskets to an extra 1% length!  
Deformation is not allowed!  
Gaps are not allowed!  
Do not stretch during installation!









2 FRK175 and FRK176 gasket machining and installation onto active sash of double casement structure











FRK175, FRK176 gasket machining and installation onto double casement structure









1 Installation of AYPCLSI130.0933K interlock plug set






Machining of AYPC.SL130.0101 and AYPC.SL130.0102 frame profiles for connection kit installation,  $L_{EF} > 6500$  mm.





5 M5x8-A2DIN7991 screw heads protrude 1 to 15 mm beyond the back plane of the frame - if supporting profile is used, perform machining accordingly.

All inserts should be installed on sealant. Only equal frame profiles can be connected.

Machining of AYPC.SL130.0103 and AYPC.SL130.0104 frame profiles for connection kit installation, L<sub>EF</sub>>6500 mm.





Machining of AYP.C.SI.130.0107 and AYP.C.SI.130.0108 frame profiles for connection kit installation,  $L_{EF} > 6500$  mm.






$X1 = L_s + L_i - 82$   
 $X2 = L_s + L_i - 42$   
 $Y1 = L_s + L_i - 110$   
 $Y2 = L_s + L_i - 70$




1 Machining of AYP.C.SI.130.0103, AYP.C.SI.130.0104 frame profiles for connector installation



Machining and installation of AYPCL.SI.130.0803 threshold profile and AYPCL.SI.130.0804 slope profile.




Machining and installation of AYPC.SL130.0805 threshold profile and AYPC.SL130.0805-01 slope profile.







Lift and Slide door integration with W62.




⑪ Machining of AYPCL.SI.130.0502 adapter and AYPCL.SI.130.0101, AYPCL.SI.130.0102, AYPCL.SI.130.0106 frame profiles




⑫ Machining of AYPCL.SI.130.0502 adapter and AYPCL.SI.130.0103, AYPCL.SI.130.0104, AYPCL.SI.130.0105 frame profiles.




⑫ Machining of AYPCL.SI.130.0502 adapter and W62 frame profile







If installed onto AYPCL.SI.130.0101 and AYPCL.SI.130.0103 frame, perform additional machining of AYPCL.SI.130.0502 adapter profile.




- AYPCL.SI.130.0101
- AYPCL.SI.130.0102
- AYPCL.SI.130.0103
- AYPCL.SI.130.0104
- AYPCL.SI.130.0105
- AYPCL.SI.130.0106



Avoid holes overlap!  
Shift Hole 2 from Hole 1 for minimum 20 mm.




Machining and installation of AYPCL.SL130.0702, AYPCL.SL160.0702 and AYPCL.SL160.0705 reinforcing profiles on sash.










1 Machining of AYPCL.SL160.0702 reinforcing profile



2 Reinforcing profile installation on sash




Machining of AYPCL.SL130.0702 reinforcing profile







Machining and installation of profiles for blind part of the structure.




Fixing lug installation




Profile machining for hardware installation. HS120



Machining of AYPLCSL130.9901 fixing profile.





Sash profile machining for transmission and handle installation.



Machining of sash profile for transmission gear and handle installation.




Machining combination depends on the handle types.






Profile machining for hardware installation. HS200 – HS270 – HS420

Machining of AYPCLSI130.9501 fixing profile.




Sash profile machining for transmission and handle installation.

Machining of sash profile for transmission gear and handle installation.




Machining combination depends on the handle types.




Profile machining for hardware installation: S270





Machining of A.YPC.SI.130.1901 fixing profile and A.YPC.SI.130.1907 decorative profile









Machining of sash profile for transmission gear and handle installation: A.YPC.SI.130.1907 decorative profile installation. Cut A.YPC.SI.130.1907 profile after all elements of A.YPC.SI.130.0970K support set are installed



Sash profile machining for transmission and handle installation.




Machining combination depends on the handle types




Profile machining for hardware installation.


11 Machining of AYPCLSL130.0202, 0203, 0204 sash profiles for installation of Comfort Close set.




12 Machining of AYPCLSL130.0901 and cap for adjusting Comfort Close set.



13 Machining of sash profiles for installation of Comfort Close mechanism hook



13 Machining of sash profiles for installation of Comfort Close mechanism hook



Variant	Calculation
A1	Les - 90
A2	Les - 78
B1	Les - 101
B2	Les - 93
C1	2xLes - 172
C2	2xLes - 165
D1	2xLes - 187
D2	2xLes - 180

Variant	Calculation
A1	Les - 62
A2	Les - 50
B1	Les - 105
B2	Les - 93
C1	2xLes - 144
C2	2xLes - 137
D1	2xLes - 187
D2	2xLes - 180







**ALUTECH SL130**  
Patio systems

# HARDWARE INSTALLATION





HS120 hardware installation

Handle transmission

Type	Hes, mm	Article	
		standard	inviso
Gr. 180	1200-1901	246866	304758
Gr. 210	1902-2201	246869	304759
Gr. 240	2202-2500	246972	304760



Sash width Les: min 650 mm – max 2000 mm  
 Sash height H<sub>es</sub>: min 1200 – max 2500 mm  
 Maximum sash weight M<sub>s</sub>: 120 kg  
 Installation height of the handle H<sub>H</sub>: 409 mm – Gr.180 (window)  
 1009 mm – Gr.210/Gr.240 (door)



Connecting rod

Type	Les, mm	Article
Gr.150	650-1360	184578
Gr.200	1361-1860	184581
Gr.250	1861-2000	184584

H<sub>es</sub> = 1001

305428

486313

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335

486335


486335

486335

486335

486335

Calculation example for HS120 hardware



Quantity according to the type of structure, pcs [ ] - optional use						Name	HS120 standard	HS120 invisio	No.	Notes		
A1, A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1	D5							
1	2	2	4	2	4	Roller set	193720		1			
1	2	2	4	2	4	Fixing set	189490		2			
1	2	2 standard	2 + 2 standard	1 + 1* see. 09.11	2 standard + 2* see. 09.11	Handle transmission	Gr.180	246866	304758	3	1200<Hes<1901	
							Gr.210	246869	304759		1902<Hes<2201	
							Gr.240	246872	304760		2202<Hes<2500	
1	2	2	4	2 see 09.11	4 see 09.11	HAUTAU handles	161 EG	206209		4.1		
							161 EG-S	206218		4.2		
[1]	[2]	[2]	[4]	[1]	[2]	External flush pull handle	223548		4.3			
1	2	2	4	2 see 09.11	4 see 09.11	MEDOS handles	PSK Dublin handle	128PSK		4.4		
							PSK Dublin handle with key	129PSK		4.5		
							PSK external flush pull handle	128PSM		4.6		
1	2	2	4	2	4	Connecting rod	Gr.150S+	184578		5	650<Les<1360	
							Gr.200S+	184581			1361<Les<1860	
							Gr.250S+	184584			1861<Les<2000	
1	2	2	4	2	4	Spacer support 7.5 mm	196433		6			
-	-	1+[1]or[2]	1+[1]or[2]	-	1+[1]or[2]	Double casement hook set	486335		7.1	for Gr.180 max [1]		
-	-	1	1	-	1	Double casement hook set with microventilation	486336		7.2			
1+[1]or[2]	2+[2]or[4]	-	2+[2]or[4]	1+[1]or[2]	-	Locking points	standard	Locking bolt with positioning	214401	-	8.1	for 1 pc. Gr.180 max [1]
1	2	-	2	1	-			Locking bolt with positioning and microventilation	214404	-	8.2	
1	2	-	2	1	-		invisio	invisio locking point set (2 pcs)	-	305428	8.3	
[1]or[2]	[2]or[4]	-	[2]or[4]	[1]or[2]	-			invisio locking point	-	305427	8.4	for 1 pc. Gr.180 max [1]
[1]	[2]	[2]	[4]	[2]	[4]	Bottom locking point	186934		9			

Quantity according to the type of structure, pcs [ ] - optional use						Name	HS120 standard	HS120 inviso	No.	Notes
A1, A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1	D5					
1	2	2	4	2	4	Fixing set	486313		10	
(According to and in case there are optional [8.1] or [8.4]) x2						Self-tapping screw	4.8x32-A2ISO14586		11	
2		4	4	4	8	Stop	187480		12	
12	24	24	48	24	48	Spacer support	AYPC.SL130.0906		13	1200<Hes<1901
14	28	28	56	28	56					1902<Hes<2500
4	8	8	16	8	16					if there is 14.1
2	4	4	8	4	8					if there is 14.2
[1]	[2]	[2]	[4]	[2]	[4]	Comfort Close mechanism	304388		14	50-120kg
[1]	[2]	[2]	[4]	[2]	[4]	Mounting set	Central ledge 100mm	485598	14.1	
							Central ledge 50mm	486334	14.2	
According to and in case there is 14.2						Bracket for Comfort Close mechanism	AYPC.SL130.1706		14.3	for 14.2
[1]	[2]	[2]	[4]	[2]	[4]	Hook for Comfort Close mechanism	305134		14.4	
-	-	-	-	[1]	[2]	Decorative cover	304816		14.5	



When choosing 4.1-4.6. handles only use of products from the same brand is acceptable.



HS200/270/420 hardware installation

standard 209738  
inviso 302889



Sash width Les: min 650 mm (1120 mm HS420) – max 2360 mm (3235 mm HS420)  
Sash height Hes: min 1200 – max 2786 mm (3400 mm with art. 209738)  
Maximum sash weight Ms: 200 kg (art. 193720); 270kg (art. 485241)  
420 kg (art. 485241 + art. 485242)  
Installation height of the handle Hh: 409 mm – Gr.180 (window)  
1009 mm – Gr.210/Gr.240 (door)

Height of handle transmission can be adjusted by cutting the rod




Handle transmission

Type	Hes, mm	Article	
		standard	inviso
Gr.180	1200-1901	1954.19	304092
Gr.210	1902-2201	1954.25	304093
Gr.240	2202-2501	1954.31	304094
Gr.270	2502-2801	1954.37	304095

Connecting rod



Type	Les, mm	Article
Gr.150	650-1360	184578
Gr.200	1361-1860	184581
Gr.250	1861-2360	184584
Gr.323	2361-3235	184587



Remove the plug, if additional locking points are used.

HS5-101  
Hes-101

Calculation example for HS200/270/420 hardware





Quantity according to the type of structure, pcs [] - optional use						Name	Article				No.	Notes			
A1, A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1	D5		HS200 standard	HS200 invisio	HS270 standard	HS270 invisio			HS420 standard	HS420 invisio	
1	2	2	4	2	4	Roller set	193720		485241			1			
1	2	2	4	2	4	Auxiliary roller set	-	-	485242			1.1	271 - 420 kg		
1	2	2	4	2	4	Fixing set	189490					2			
1	2	2 standard	2 + 2 standard	2 see 09.11	2 + 2* see 09.11	Handle transmission	Gr.180	195419	304092	195419	304092	195419	304092	3	1200<Hes<1901 *195419
							Gr.210	195425	304093	195425	304093	195425	304093		1902<Hes<2201 *195425
							Gr.240	195431	304094	195431	304094	195431	304094		2202<Hes<2501 1 *195431
							Gr.270	195437	304095	195437	304095	195437	304095		2502<Hes<2801 1 *195437
1	2	2*	2 + 2*	1	2*	Handle transmission extension	209738	302889	209738	302889	209738	302889	3.1	2802<Hes<3400 *209738	
1	2	2	4	2 see 09.11	4 see 09.11	HAUTAU handle set	Handle	234410				4.1			
							Handle Pz/l	234431				4.2			
							Handle Pz/IE H	185179				4.3			
1	2	2	4	2 see 09.11	4 see 09.11	MEDOS handles	Internal handle without cylinder hole	128HS1				4.4	Quantity of chosen handle combination is specified according to page 09.05		
							Internal handle with cylinder hole	128HS2				4.5			
							External handle with cylinder hole	128HS3				4.6			
							External flush pull handle	129HS				4.7			
-	-	-	-	1 see 09.11	2 see 09.11	Handle fastening kit	225496				4.8	for 4.1 or 4.4			
1	2	2	4	2	4	Connecting rod	Gr.150S+	184578				5	650<Les<1360		
							Gr.200S+	184581					1361<Les<1860		
							Gr.250S+	184584					1861<Les<2360		
							Gr.323S+	184587					2361<Les<3235		

Quantity according to the type of structure, pcs [ ] - optional use						Name	HS200	HS200	HS270	HS270	HS420	HS420	No.	Notes		
A1, A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1	D5		standard	inviso	standard	inviso	standard	inviso				
						Article										
1	2	2	4	2	4	Spacer support 7.5 mm	196433						6			
-	-	1+{1}or{2}	1+{1}or{2}	-	1+{1}or{2}	Double casement hook set	486335						7.1	for Gr.180 max {1} 2802<Hes<340 0		
-	-	1	1	-	1		486336								7.2	
1+{1}or{2}	2+{2}or{4}	-	2+{2}or{4}	1+{1}or{2}	-		Locking points	standard	Locking bolt with positioning	214401	-	214401	-	214401	-	8.1
1	2	-	2	1	-	Locking bolt with positioning and microventilation			214404	-	214404	-	214404	-	8.2	
1	2	-	2	1	-	inviso locking point set (2pcs)			-	305428	-	305428	-	305428	8.3	
{1}or{2}	{2}or{4}	-	{2}or{4}	{1}or{2}	-	inviso		inviso locking point	-	305427	-	305427	-	305427	8.4	for 1pc. Gr.180 max {1} 2802<Hes<340 0
1	2	-	2	1	-			Bottom locking point						186934	9	
{1}	{2}	{2}	{4}	{2}	{4}			Fastening kit						486313	10	271 - 420 kg 2802<Hes<340 0
(According to and in case there are optional (8.1) or (8.4) x2						Self-tapping screw	4.8x32-A2IS014586						11			
2	4 2 for A3	4	4	4	8	Stop	187480						12			
12	24	24	48	24	48	Spacer support	AYPC.SL130.0906						13	1200<Hes<1901		
14	28	28	56	28	56									1902<Hes<2801		
4	8	8	16	8	16									271 - 420 kg		
3	6	6	12	6	12									2802<Hes<340 0		
4	8	8	16	8	16									if there is 17.1		
2	4	4	8	4	8									if there is 17.2		
According to and in case there is 4.2 or 4.5 handle						45x10 cylinder	5304.00						14.1	for 4.2. 4.5		
According to and in case there is 4.3 or 4.6 handle						45x45 cylinder	5066.00						14.2	for 4.3. 4.6		
1	2	2	4	2	4	Micralift	<200 kg - 239654 >200 kg - 239657						15	except for Gr.180		
{1}	{2}	{2}	{4}	{2}	{4}	Gas lift	>120 kg- 247164						16	except for Gr.180		
{1}	{2}	{2}	{4}	{2}	{4}	Comfort Close mechanism	≤200 kg- 304388 >200..300 kg- 304389						17			
{1}	{2}	{2}	{4}	{2}	{4}	Mounting kit	Central ledge 100 mm	485598						17.1		
							Central ledge 50 mm	486334						17.2		
According to and in case there is 17.2						Bracket for Comfort Close mechanism	AYPC.SL130.1706						17.3			
{1}	{2}	{2}	{4}	{2}	{4}	Hook for Comfort Close mechanism	305134						17.4			
-	-	-	-	{1}	{2}	Decorative cover	304816						17.5			

When choosing 4.1-4.7. handles only use of products from the same brand is acceptable.



Calculation example for S270 hardware



When choosing 3.1-3.8. handles only use of products from the same brand is acceptable.

Quantity according to the type of structure, pcs [ ] - optional use						Name	S270 standard	No.	Application	
A1	A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1					D5
1	2	2	4	2	4	Roller set	486356	1		
1	2	1 see 09.11	3	1 see 09.11	1 see 09.11	Handle transmission	Gr.50	215529	2.1	650<Hes<1850
							Gr.200	215532	2.2	1851<Hes<2700
1	2	1 see 09.11	3	1 see 09.11	1 see 09.11	HAUTAU handles	161 EG	206209	3.1	
							161 EG-S	206218	3.2	
							161 EG-Pz/I	206227	3.3	1851<Hes<2700
							160 EG-Pz/A	163275	3.4	Only for 3.3
							External flush pull handle	223548	3.5	
1	2	1 see 09.11	3	1 see 09.11	1 see 09.11	MEDOS handles	PSK Dublin handle	128PSK	3.6	
							PSK Dublin handle with key	129PSK	3.7	
							PSK external flush pull handle	128PSM	3.8	
[1]	[2]	[2]	[4]	[1]	[1]	According to and in case there is 3.3	Lockcase	203130	3.9	Only for 3.4
-	-	2 [1] or [2]	2 [1] or [2]	-	2 [1] or [2]	Double casement hook set	486335	4	1851<Hes<2700	
2	4	-	4	2	-	Locking bolt with positioning	214401	5	1851<Hes<2700	
[1] or [2]	[2] or [4]	-	[2] or [4]	[1] or [2]	-					
1	2	2	4	2	4	Fastening kit	486313	6		
According to and in case there are optional [5] x2						Self-tapping screw	4.8x32-A2IS014586	7	1851<Hes<2700	
2		4	4	4	8	Stop	187480	8		
8	16	18	34	12	26	Spacer support	AYPC.SL130.0906	9	650<Hes<1850	
12	24	22	46	16	30				1851<Hes<2700	
-	-	-	-	-	-					


Quantity according to the type of structure, pcs [ ] - optional use						Name	S270 standard	No.	Application
A1, A2, C1	A3, A5, A6, C3	A7, A8, C4	A9, A10	D1	D5		Article		
According to and in case there is 3.3						40/10 cylinder	DBCY-40/10	10.1	
According to and in case there is 3.4						40/40 cylinder	DBCY-40/40	10.2	
-	-	1	1	-	1	Support set	AYPC.SL130.0910K	11	650<Hes<1850
-	-	1 + [1]	1 + [1]	-	1 + [1]				1851<Hes<2700
-	-	1	1	-	1	Decorative profile	AYPC.SL130.1907	12	1pc. 2.5 m Long

Microlift/Gaslift installation on lift-and-slide sashes


<200 kg

>200 kg


>120 kg



239654



239657




247164





H<sub>ES</sub> >1902 mm

Handle transmission

Type	Article
Gr. 210	195419
Gr. 240	195425
Gr. 270	195431






Installation of single-sided handle onto the fixed sash




Installation of standard locking elements. HS120/200/270/420

Type	A1, mm	A2, mm	B1, mm	B2, mm	C1, mm	C2, mm	D1, mm	D2, mm	X, mm
HS120 standard									
Gr.180	-	-	588	612	988	1012	-	-	-
Gr.210	738	762	1188	1212	1588	1612	-	-	-
Gr.240					1888	1912	-	-	-
HS200/270/420 standard									
Gr.180	-	-	588	612	988	1012	-	-	-
Gr.210	738	762	1188	1212	1588	1612	-	-	-
Gr.240					1888	1912	Hes-323	Hes-299	Hes-701
Gr.270					2188	2212			




Position the locking points along the hardware groove of the frame.

Remove the plug, if additional locking points are used.




Set the size from the top of AYP.C.SL160.1950 guide rail.



Installation of invisio locking elements. HS120/200/270/420

Type	A1, mm	A2, mm	B1, mm	B2, mm	C1, mm	C2, mm	D1, mm	D2, mm	X, mm
HS120 invisio									
Gr. 180	-	-	546	654	946	1054	-	-	-
Gr. 210	696	804	1146	1254	1546	1654	-	-	-
Gr. 240					1846	1954	-	-	-
HS200/270/420 invisio									
Gr. 180	-	-	546	654	946	1054	-	-	-
Gr. 210	696	804	1146	1254	1546	1654	-	-	-
Gr. 240					1846	1954	Hes -365	Hes -257	Hes -701
Gr. 270					2146	2254			




If strike plates are installed on AYPCL130.0105, AYPCL130.0106, AYPCL130.0109 frame, cut AYPCL130.0806 cover cap after installation and adjustment of strike sets.

Position the locking points along the hardware groove of the frame.






Set the size from the top of AYPCL160.1950 guide rail.



Installation of locking elements. S270

Type	A1, mm	A2, mm	B1, mm	B2, mm	C1, mm	C2, mm	D1, mm	D2, mm
S270 standard								
Gr.50	-	-	167	143	133	157	-	-
Gr.200	759	735	259	235	291	315	741	765

Gr.200 standard





Position the locking points along the hardware groove of the frame.



Installation of locking elements onto double casement profile. HS120/200/270/420

Double casement hook set with spacer support set art. 486335 Double casement hook set with microventilation with spacer support set art. 486336




209738 for 195431 and 195437



installed only in the bottom



Install fixing plate on the transmission according to marks on the housing



AYPC.SL130.0205


AYPC.SL130.1901

Adjustment of locking elements

Remove the required number of spacer supports

Permanent position

Add the required number of spacer supports



Installation of locking elements onto double casement profile. S270




Install the supports and fix by marks on their housing.

Support set art. AYPC.SL130.0910K

Double casement hook set with spacer support set art. 486335



Decorative profile art. AYPC.SL130.1907




Install fixing plate and fix with hook by marks on the support housing.

AYPC.SL130.0205 fixed sash


AYPC.SL130.1907





\* - After adjustment of locking elements




Installation of Comfort Close mechanism of lift and slide door



≤200 kg – 304388 (black colour of housing)  
200-300 kg – 304389 (grey silver colour of housing)



+ / - 5mm



+ 3mm



485598



\* - Remove before sash installation into the frame!




Raise gas lift before installation

\*304388  
\*304389

\*AYPC.SL130.0901  
from AYPC.SL130.094.OHS set  
\*AYPC.SL130.0801  
AYPC.SL130.0201

AYPC.F50.0932





AYPC.SL130.0906

AYPC.SL130.0906

AYPC.SL130.0201

\*485598




CA-500.200







After installation and fixing of 485598 mounting kit

Installation of Comfort Close mechanism of lift and slide door





≤200 kg - 304388 (black colour of housing)  
200-300 kg - 304389 (grey silver colour of housing)



Raise gas lift before installation


\*304388  
\*304389



After pre-fixing the bracket to the bottom pair of self-tapping screws

\*3.9x13-A2ISO14585 from 486334 set

\*AYP.C.SL130.1706



\* - Remove before sash installation into the frame!